

UAC-B122-AF28M-W

UAC-B122-AF28M-W Color Hunter Camera 2 MP

- 2MP high quality imaging
- TVI/AHD/CVI/CVBS
- Supports white light illumination, 24/7 color images
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages
- Built-in microphone for high quality audio transmission via coaxial cables
- Supports digital defog
- Metal front face and housing

| | |
|-------------------|------------|
| Type | Analog |
| Megapixel | 2 MP |
| Objective | Motionless |
| Focus | 2.8 mm |
| Lighting | LED |
| Lighting distance | 40 m |
| Microphone | Mic |
| Protection | IP67 |
| Material | Metal |



Detailed

| | |
|----------------------|--|
| Model | UAC-B122-AF28M-W |
| Sensor | |
| Pixel | 2MP |
| Size | 1/2.9" |
| Minimum illumination | 0.005 lux (F1.6, AGC ON) 0 lux (white light on) |
| Lens | |
| Lens | 2.8mm |

| | |
|-------------------------|---|
| Lens mount | M12 |
| Angle of view | H: 101.5° V: 56.9° D: 117.4° |
| Illuminator | |
| Illuminator | Two white-light illuminators |
| Illumination distance | 40m |
| Lifetime | ≥60,000 hours |
| Video | |
| Resolution | 1080P: 1920(H)×1080(V) 720P: 1280(H) ×720(V) |
| Frame rate | TVI/AHD/CVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC |
| Shutter time | PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s |
| Image | |
| Exposure mode | Four modes: Global (default), BLC, HLC, DWDR |
| Day/Night | 24/7 color images |
| Digital noise reduction | 2D/3D |
| White balance | Two modes: Auto (default), Manual |
| WDR | DWDR |
| Flip | Supports 180° horizontal flip, 180° vertical flip |
| Defog | Digital Defog |
| Audio | |
| Microphone | Built-in Mic |
| Camera audio | TVI: 1080P@25fps, 1080P@30fps CVI: 1080P@25fps, 1080P@30fps |
| Interface | |
| | |

| | |
|------------------------------|---|
| Power | 5.5mm power interface |
| Video output | BNC, supports TVI/AHD/CVI/CVBS |
| Operating environment | |
| Temperature | -30°C to 60°C (-22°F to 140°F) |
| Humidity | ≤95% (RH, non-condensing) |
| Surge protection | 4kV |
| Ingress protection | IP67 |
| General | |
| Power | DC 12V (±25%), with reverse polarity protection, Max 3.12W |
| Mount | 3D bracket supplied, surface mount (default), optional junction box |
| Dimensions | 157.4mm*66.5mm*66.5mm (L*W*H) |
| Material | Metal |
| Weight | 279g (0.62lb) |
| Certification | CB, CE, FCC, UL |