

UAC-B125-AF40M-W

Kamera UAC-B125-AF40M-W Color Hunter 5 MP 4mm

- 5MP high quality imaging
- TVI/AHD/CVI/CVBS
- Supports white light illumination, 24/7 color images
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages
- Built-in microphone for high quality audio transmission via coaxial cables
- Metal front face and housing

|                       |        |
|-----------------------|--------|
| Növ                   | Analoq |
| Megapixel             | 5 MP   |
| Obyektiv              | Sabit  |
| Fokus                 | 4      |
| İşıqlandırma          | LED    |
| İşıqlandırma məsafəsi | 40 m   |
| Mikrofon              | Mic    |
| Qoruma                | IP67   |
| Material              | Metal  |



Ətraflı

|                      |                                                    |
|----------------------|----------------------------------------------------|
| Model                | UAC-B125-AF40M-W                                   |
| Sensor               |                                                    |
| Pixel                | 5MP                                                |
| Size                 | 1/2.7"                                             |
| Minimum illumination | 0.005 lux (F1.4, AGC ON)<br>0 lux (white light on) |
| Lens                 |                                                    |
| Lens                 | 4.0mm                                              |
|                      |                                                    |

|                         |                                                                                                                                                                                                                                             |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Lens mount              | M12                                                                                                                                                                                                                                         |
| Angle of view           | H: 89.6° V: 48.3° D: 106.4°                                                                                                                                                                                                                 |
| <b>Illuminator</b>      |                                                                                                                                                                                                                                             |
| Illuminator             | Two white-light illuminators                                                                                                                                                                                                                |
| Illumination distance   | 40m                                                                                                                                                                                                                                         |
| Lifetime                | ≥60,000 hours                                                                                                                                                                                                                               |
| <b>Video</b>            |                                                                                                                                                                                                                                             |
| Resolution              | 5MP@25fps: 2880(H)×1620(V); 5MP@20fps: 2592(H)×1944(V); 5MP@12.5fps: 2592(H)×1944(V)<br>4MP: 2560(H)×1440(V)<br>1080P: 1920(H)×1080(V)                                                                                                      |
| Frame rate              | TVI: 5MP@20fps (default), 5MP@12.5fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps<br>AHD: 5MP@20fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps<br>CVI: 5MP@25fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps<br>CVBS: PAL/NTSC |
| Shutter time            | PAL: 1/25s-1/50000s<br>NTSC: 1/30s-1/50000s                                                                                                                                                                                                 |
| <b>Image</b>            |                                                                                                                                                                                                                                             |
| Exposure mode           | Four modes: Global (default), BLC, HLC, DWDR                                                                                                                                                                                                |
| Day/Night               | 24/7 color images                                                                                                                                                                                                                           |
| Digital noise reduction | 2D                                                                                                                                                                                                                                          |
| White balance           | Two modes: Auto (default), Manual                                                                                                                                                                                                           |
| WDR                     | DWDR                                                                                                                                                                                                                                        |
| Flip                    | Supports 180° horizontal flip, 180° vertical flip                                                                                                                                                                                           |
| <b>Audio</b>            |                                                                                                                                                                                                                                             |
| Microphone              | Built-in Mic                                                                                                                                                                                                                                |
| Camera audio            | TVI: 5MP@20fps, 5MP@12.5fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps<br>CVI: 5MP@25fps, 4MP@30fps, 4MP@25fps                                                                                                                         |

|                              |                                                                     |
|------------------------------|---------------------------------------------------------------------|
| <b>Interface</b>             |                                                                     |
| Power                        | 5.5mm power interface                                               |
| Video output                 | BNC, supports TVI/AHD/CVI/CVBS                                      |
| <b>Operating environment</b> |                                                                     |
| Temperature                  | -30°C to 60°C (-22°F to 140°F)                                      |
| Humidity                     | ≤95% (RH, non-condensing)                                           |
| Surge protection             | 4kV                                                                 |
| Ingress protection           | IP67                                                                |
| <b>General</b>               |                                                                     |
| Power                        | DC12V (±25%), with reverse polarity protection. Max 3.28W           |
| Mount                        | 3D bracket supplied, surface mount (default), optional junction box |
| Dimensions                   | 157.4mm*66.5mm*66.5mm (L*W*H)                                       |
| Material                     | Metal                                                               |
| Weight                       | 279g (0.62lb)                                                       |
| Certification                | CB, CE, FCC, UL                                                     |