

IPC2122LB-SF28-A

IPC2122LB-SF28-A 2MP Mini Fixed Bullet Network Camera

- High quality image with 2MP, 1/2.8"CMOS sensor
- 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps
- Ultra 265, H.265, H.264
- Smart IR, up to 30m (98ft) IR distance
- Day/night functionality
- 2D/3D DNR (Digital Noise Reduction)
- IP67 protection
- Support PoE power supply
- 3-Axis

|                       |       |
|-----------------------|-------|
| Növ                   | IP    |
| Megapixel             | 2 MP  |
| Obyektiv              | Sabit |
| Fokus                 | 2.8   |
| İşıqlandırma          | İR    |
| İşıqlandırma məsafəsi | 30 m  |
| Qoruma                | IP67  |
| Material              | Metal |



Ətraflı

|                   |                                               |            |              |
|-------------------|-----------------------------------------------|------------|--------------|
| Model             | IPC2122LB-SF28-A                              |            |              |
| Camera            |                                               |            |              |
| Sensor            | 1/2.8", 2.0 megapixel, progressive scan, CMOS |            |              |
| Lens              | 2.8mm@F2.0                                    |            |              |
| DORI Distance     | Lens (mm)                                     | Detect (m) | Observ e (m) |
|                   | 2.8                                           | 43.4       | 17.4         |
| Angle of View (H) | 106.7°                                        |            |              |
|                   |                                               |            |              |

|                         |                                                                                                                                                                                     |                |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| Angle of View (V)       | 57.1°                                                                                                                                                                               |                |
| Angle of View (O)       | 115.7°                                                                                                                                                                              |                |
| Adjustment angle        | Pan: 0° ~ 360°                                                                                                                                                                      | Tilt: 0° ~ 90° |
| Shutter                 | Auto/Manual, 1 ~ 1/100000s                                                                                                                                                          |                |
| Minimum Illumination    | Colour: 0.01Lux (F2.0, AGC ON)<br>0Lux with IR on                                                                                                                                   |                |
| Digital noise reduction | 2D/3D DNR                                                                                                                                                                           |                |
| Day/Night               | IR-cut filter with auto switch (ICR)                                                                                                                                                |                |
| S/N                     | >52dB                                                                                                                                                                               |                |
| IR Range                | Up to 30m (98ft) IR range                                                                                                                                                           |                |
| Wavelength              | 850nm                                                                                                                                                                               |                |
| IR On/Off Control       | Auto/Manual                                                                                                                                                                         |                |
| Defog                   | Digital Defog                                                                                                                                                                       |                |
| WDR                     | DWDR                                                                                                                                                                                |                |
| Video                   |                                                                                                                                                                                     |                |
| Video Compression       | Ultra 265, H.265, H.264                                                                                                                                                             |                |
| H.264 code profile      | Baseline profile, Main profile, High profile                                                                                                                                        |                |
| Frame Rate              | Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps<br>Sub Stream: D1 (720*576), Max 30fps; 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; |                |
| Video Bit Rate          | 128 Kbps~16 Mbps                                                                                                                                                                    |                |
| OSD                     | Up to 4 OSDs                                                                                                                                                                        |                |
| Privacy Mask            | Up to 4 areas                                                                                                                                                                       |                |
| ROI                     | Up to 8 areas                                                                                                                                                                       |                |
| Motion Detection        | Up to 4 areas                                                                                                                                                                       |                |
| Image                   |                                                                                                                                                                                     |                |

|                         |                                                                               |
|-------------------------|-------------------------------------------------------------------------------|
| White Balance           | Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2                               |
| Digital noise reduction | 2D/3D DNR                                                                     |
| Smart IR                | Supported                                                                     |
| Flip                    | Normal/Vertical/Horizontal/180°                                               |
| Dewarping               | N/A                                                                           |
| HLC                     | Supported                                                                     |
| BLC                     | Supported                                                                     |
| Network                 |                                                                               |
| Protocols               | IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP |
| Compatible Integration  | API                                                                           |
| Client                  | EZStation<br>EZView<br>EZLive                                                 |
| Web Browser             | Plug-in free live view: Chorme 57.0+, Firefox 58.0+, Edge 16+                 |
| Interface               |                                                                               |
| Network                 | 10/100M Base-TX Ethernet                                                      |
| Certifications          |                                                                               |
| Certifications          | CE: EN 60950-1<br>UL: UL60950-1<br>FCC: FCC Part 15                           |
| General                 |                                                                               |
| Power                   | DC 12V±25%, PoE (IEEE 802.3af)                                                |
|                         | Power consumption: Max 5.5W                                                   |
| Dimensions (L × W × H)  | 161 × 63 ×62mm (6.4" × 2.5" × 2.4")                                           |
| Net Weight              | 0.27kg (0.60lb)                                                               |

|                      |                                                                  |
|----------------------|------------------------------------------------------------------|
| Material             | Metal + Plastic                                                  |
| Working Environment  | -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing) |
| Strorage Environment | -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing) |
| Surge Protection     | 4KV                                                              |
| Ingress Protection   | IP67                                                             |
| Reset Button         | N/A                                                              |