

IPC2122LB-ADF40KM-G

IPC2122LB-ADF40KM-G 2MP HD WDR Fixed IR Bullet Network Kamera 4mm

- High quality image with 2MP, 1/2.7"CMOS sensor
- 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps
- Ultra 265, H.265, H.264, MJPEG
- 120dB true WDR technology enables clear image in strong light scene
- Support 9:16 Corridor Mode
- Built-in Mic
- Smart IR, up to 30m (98ft) IR distance
- Supports 128 G Micro SD card
- Support PoE power supply
- 3-Axis

|                       |       |
|-----------------------|-------|
| Növ                   | IP    |
| Megapixel             | 2 MP  |
| Obyektiv              | Sabit |
| Fokus                 | 4     |
| İşıqlandırma          | İR    |
| İşıqlandırma məsafəsi | 30 m  |
| Mikrofon              | Mic   |
| Qoruma                | IP67  |
| Material              | Metal |



Ətraflı

|                      |                                                      |
|----------------------|------------------------------------------------------|
| Model                | IPC2122LB-ADF40KM-G                                  |
| Camera               |                                                      |
| Sensor               | 1/2.7", 2.0 megapixel, progressive scan, CMOS        |
| Minimum Illumination | Colour: 0.01Lux ( F2.0, AGC ON)<br>0Lux with IR      |
| Day/Night            | IR-cut filter with auto switch (ICR)                 |
| Shutter              | Auto/Manual, 1 ~ 1/100000s                           |
| Adjustment Angle     | Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360° |

|                    |                                                                                                                                                                                                                    |            |             |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-------------|
| S/N                | >52dB                                                                                                                                                                                                              |            |             |
| WDR                | 120dB                                                                                                                                                                                                              |            |             |
| Lens               |                                                                                                                                                                                                                    |            |             |
| Lens Type          | 2.8mm and 4.0mm @2.0, Fixed-focal                                                                                                                                                                                  |            |             |
| Lens Mount         | M12                                                                                                                                                                                                                |            |             |
| Angle of View (H)  | 112.9°                                                                                                                                                                                                             |            |             |
| Angle of View (V)  | 59.1°                                                                                                                                                                                                              |            |             |
| Angle of View (O)  | 121.2°                                                                                                                                                                                                             |            |             |
| DORI               |                                                                                                                                                                                                                    |            |             |
| DORI Distance      | Lens (mm)                                                                                                                                                                                                          | Detect (m) | Observe (m) |
|                    | 4                                                                                                                                                                                                                  | 60.0       | 16.8        |
| Illuminator        |                                                                                                                                                                                                                    |            |             |
| IR Range           | Up to 30m (98ft) IR range                                                                                                                                                                                          |            |             |
| Wavelength         | 850nm                                                                                                                                                                                                              |            |             |
| IR On/Off Control  | Auto/Manual                                                                                                                                                                                                        |            |             |
| Video              |                                                                                                                                                                                                                    |            |             |
| Video Compression  | Ultra 265, H.265, H.264, MJPEG                                                                                                                                                                                     |            |             |
| H.264 code profile | Baseline profile, Main profile, High profile                                                                                                                                                                       |            |             |
| Frame Rate         | Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps<br>Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360,Max 30fps;<br>2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; |            |             |
| Video Bit Rate     | 128 Kbps~6144 kbps                                                                                                                                                                                                 |            |             |
| U-code             | Supported                                                                                                                                                                                                          |            |             |
| 9:16 Corridor Mode | Supported                                                                                                                                                                                                          |            |             |
| OSD                | Up to 4 OSDs                                                                                                                                                                                                       |            |             |
| Privacy Mask       | Up to 4 areas                                                                                                                                                                                                      |            |             |

|                         |                                                                                                                                                                                   |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ROI                     | Up to 8 areas                                                                                                                                                                     |
| Motion Detection        | Up to 4 areas                                                                                                                                                                     |
| <b>Image</b>            |                                                                                                                                                                                   |
| White Balance           | Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2                                                                                                                                   |
| Image Setting           | Image rotation, brightness, saturation, contrast, sharpness, gain adjustable by web browser                                                                                       |
| Digital Noise Reduction | 2D/3D DNR                                                                                                                                                                         |
| Smart IR                | Supported                                                                                                                                                                         |
| Flip                    | Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise                                                                                                                    |
| Dewarping               | N/A                                                                                                                                                                               |
| HLC                     | Supported                                                                                                                                                                         |
| BLC                     | Supported                                                                                                                                                                         |
| Defog                   | Digital Defog                                                                                                                                                                     |
| <b>Audio</b>            |                                                                                                                                                                                   |
| Audio Compression       | G.711                                                                                                                                                                             |
| Suppression             | Supported                                                                                                                                                                         |
| Sampling Rate           | 8KHZ                                                                                                                                                                              |
| <b>Storage</b>          |                                                                                                                                                                                   |
| Edge Storage            | Micro SD, up to 128GB                                                                                                                                                             |
| Network Storage         | ANR,NAS(NFS)                                                                                                                                                                      |
| <b>Network</b>          |                                                                                                                                                                                   |
| Protocols               | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, SNMP                                                         |
| Compatible Integration  | ONVIF (Profile S, Profile G, Profile T), API , SDK                                                                                                                                |
| User/Host               | Up to 32 users. 2 user levels: administrator and common user                                                                                                                      |
| Security                | Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest |

|                        |                                                                             |
|------------------------|-----------------------------------------------------------------------------|
|                        | authentication for ONVIF                                                    |
| Client                 | EZStation<br>EZView<br>EZLive                                               |
| Web Browser            | Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below |
|                        | Plug-in free live view: Chorme 57.0+, Firefox 58.0+, Edge 16+               |
| <b>Interface</b>       |                                                                             |
| Network                | 1 * RJ45 10M/100M Base-TX Ethernet                                          |
| Built-in Mic           | Supported                                                                   |
| Certifications         |                                                                             |
| EMC                    | FCC: FCC Part 15                                                            |
| Safety                 | CE: EN 60950-1<br>UL: UL60950-1<br>IEC 60950-1                              |
| <b>General</b>         |                                                                             |
| Power                  | DC 12V±25%, PoE (IEEE 802.3af)                                              |
|                        | Power consumption: Max 7.0W                                                 |
| Power Interface        | Ø 5.5mm coaxial power plug                                                  |
| Dimensions (L × W × H) | 165 × 63 × 62mm (6.5" × 2.5" × 2.5")                                        |
| Weight                 | 0.39kg (0.86lb)                                                             |
| Material               | Metal + plastic                                                             |
| Working Environment    | -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)            |
| Strorage Environment   | -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)            |
| Surge Protection       | 4KV                                                                         |
| Reset Button           | N/A                                                                         |
| Ingress Protection     | Ingression protection: IP67                                                 |

