

XVR301-04F

Video recorder XVR301-04F 1 HDD 4-Ch 1U Digital Video Recorder

- Support H.265/H.264 video formats
- Support audio over coaxial cable (only for TVI cameras)
- Control the dual-light of UNV analog cameras under TVI
- Support analog camera upgrade over coaxial cable
- Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
- 4/8/16-channel BNC input
- Support 1-ch HDMI output, 1-ch VGA output at up to 1920*1080
- HDMI and VGA simultaneous output
- Long transmission distance over coaxial cable
- Support mainstream cameras of ONVIF and RTSP protocols

Number of channels	4 channel
Type	XVR
Megapixel	6 MP
Max HDD count	1 HDD
Max HDD capacity	6 TB



Detailed

Video/Audio Input	Description
IP Video Input	2-ch
Analog Video Input	XVR301-04F:4-ch, BNC XVR301-16F:16-ch, BNC XVR301-08F:8-ch, BNC
Max IP Video Input	XVR301-04F:6-ch XVR301-16F:18-ch XVR301-08F:10-ch

Supported Analog Camera Types	Support AHD input: 1080P@30fps 720P@30fps Support TVI input: 1080P@30fps 720P@30fps Support CVI input: 1080P@30fps 720P@30fps Support CVBS input
Video/Audio Output	Description
HDMI Output	HDMI:1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
VGA Output	VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Live View Display	XVR301-04F:HDMI/VGA: 1/4/6/8/9 XVR301-16F:HDMI/VGA: 1/4/6/8/9/25 XVR301-08F:HDMI/VGA: 1/4/6/8/9/16
Encoding/Decoding	Description
Recording Resolution	1080P Lite/720P/D1
Recording Frame Rate	XVR301-04F:Main stream: 1080P Lite@25fps Sub stream: D1@25fps Main stream: 720P@30fps Sub stream: D1@30fps XVR301-16F:Main stream: 1080P Lite@12fps Sub stream: D1@12fps Main stream: 720P@15fps Sub stream: D1@15fps XVR301-08F:Main stream: 1080P Lite@15fps Sub stream: D1@12fps Main stream: 720P@15fps Sub stream: D1@15fps
Audio Sample Rate	8KHz,16 bit per channel
Audio Bit Rate	64Kbps per channel
Decoding Capability	XVR301-04F:Analog:4 x 1080P Lite@25, 4 x 720P@30 IP: 1 x 6MP@20, 2 x 1080P@30 XVR301-16F:Analog:16x 1080P Lite@12, 16x 720P@15 IP: 1 x 8MP@30, 2 x 4MP@30, 4 x 1080P@30, 8 x 720P@30,16 x D1@30 XVR301-08F:Analog:8x 1080P Lite @15, 8x 720P @15 IP: 1 x 6MP@20, 2 x 1080P@30
Two-way Audio	Description
Two-way Audio	NA
Analog Snapshot	Description
FTP/Schedule/Event Snapshot	XVR301-04F:FTP/Event snapshot:4-ch snapshot, up to 704*576 resolution,

	Schedule snapshot:not supported XVR301-16F:FTP/Event snapshot:16-ch snapshot, up to 704*576 resolution, Schedule snapshot:not supported XVR301-08F:FTP/Event snapshot:8-ch snapshot, up to 704*576 resolution, Schedule snapshot:not supported
Network	Description
Incoming Bandwidth	XVR301-04F:24Mbps (Up to 32Mbps after all analog channel conversion) XVR301-16F:24Mbps (Up to 56Mbps after all analog channel conversion) XVR301-08F:24Mbps (Up to 40Mbps after all analog channel conversion)
Outgoing Bandwidth	XVR301-04F:48Mbps XVR301-16F/XVR301-08F:64Mbps
Remote Users	128
Protocols	TCP/IP;P2P;UPnP;NTP;DHCP;HTTP;HTTPS;DNS;DDNS;SMTP
Browser(Plugin)	IE(IE10/11) Firefox (version 52.0 and above) Chrome(version 45 and above) Edge(version 79 and above)
Smart	Description
Analog Smart by XVR	Ultra Motion Detection(UMD)
VCA Search	Behavior Search
Smart Functions by XVR	XVR301-04F:4-ch(UMD) XVR301-16F/XVR301-08F:8-ch(UMD)
Alarm	Description
General Alarm	Motion
Alert Alarm	IP Conflict;Network Disconnected;Disk offline;Disk Abnormal;Illegal Access;Hard Disk Space Low;Hard Disk Full;Recording/Snapshot Abnormal
Hard Disk	Description
SATA	1 SATA interface
Capacity	Up to 6TB for each HDD
External Interface	Description
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface

USB	Rear panel: 2 x USB2.0
Power Supply	DC 12V/1.5A
Working Environment	Description
Working Temperature	-10°C ~ + 55°C (+14°F ~ +131°F)
Working Humidity	≤ 90% RH(non-condensing)
Power Consumption (without HDD)	≤ 10W
Dimensions	Description
Weight (without HDD)	XVR301-04F/XVR301-08F:≤0.6 Kg (1.32lb) XVR301-16F:≤0.85 Kg (1.87lb)
Dimensions	XVR301-04F/XVR301-08F:190mm × 202mm × 42mm (7.5" × 7.9" × 1.6") XVR301-16F:253mm × 212mm × 42mm (10.0" × 8.4" × 1.7")
Certification	Description
Certification	CE, FCC, UL, RoHS, WEEE
CE	EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035
FCC	Part15 Subpart B