

XVR301-04G3

Video Recorder XVR301-04G3 1 HDD 4-Ch 1U Digital Video Recorder

- Support H.265/H.264 video formats
- Support audio over coaxial cable (only for TVI cameras)
- Control the dual-light of UNV analog cameras under TVI
- Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
- 4/8/16-channel BNC input
- Support 1-ch HDMI output, 1-ch VGA output at up to 1920*1080
- HDMI and VGA simultaneous output
- Long transmission distance over coaxial cable
- Support mainstream cameras of ONVIF and RTSP protocols

Number of channels	4 channel
Type	XVR
Megapixel	5 MP
Max HDD count	1 HDD
Max HDD capacity	16 TB



Detailed

Video/Audio Input	Description
IP Video Input	XVR301-04G3:2-ch XVR301-08G3:4-ch XVR301-16G3:8-ch
Analog Video Input	XVR301-04G3:4-ch, BNC XVR301-08G3:8-ch, BNC XVR301-16G3:16-ch, BNC
Max IP Video Input	XVR301-04G3:6-ch XVR301-08G3:8-ch XVR301-16G3:16-ch

Supported Analog Camera Types	<p>XVR301-04G3:Support AHD input: 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps Support TVI input: 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps Support CVI input: 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps Support CVBS input XVR301-08G3:Support AHD input: 5MP@12.5fps 4MP@15fps 1080P@30fps 720P@30fps Support TVI input: 5MP@12.5fps 4MP@15fps 1080P@30fps 720P@30fps Support CVI input: 4MP@15fps 1080P@30fps 720P@30fps Support CVBS input XVR301-16G3:Support AHD input: 5MP@12.5fps 4MP@15fps 1080P@30fps 720P@30fps Support TVI input: 5MP@12.5fps 4MP@15fps 1080P@30fps 720P@30fps Support CVI input: 1080P@30fps 720P@30fps Support CVBS input</p>
RCA Audio Input	1-ch
Video/Audio Output	Description
HDMI Output	HDMI:1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
VGA Output	VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
RCA Audio Output	1-ch
Live View Display	XVR301-04G3:HDMI/VGA: 1/4/6/8/9 XVR301-08G3:HDMI/VGA: 1/4/6/8/9/16 XVR301-16G3:HDMI/VGA: 1/4/6/8/9/25
Encoding/Decoding	Description

Recording Resolution	XVR301-04G3:5MP Lite/4MP Lite/1080P/720P/D1 XVR301-08G3:5MP Lite/4MP Lite/1080P Lite/720P/D1 XVR301-16G3:5MP Lite/4MP Lite /1080P Lite/720P/D1
Recording Frame Rate	XVR301-04G3:Main stream: 5MP Lite@12fps Sub stream: D1@12fps Main stream: 4MP Lite@15fps Sub stream: D1@15fps Main stream: 1080P@15fps Sub stream: D1@15fps Main stream: 720P@25fps Sub stream: D1@25fps XVR301-08G3/XVR301-16G3:Main stream: 5MP Lite@6fps Sub stream: D1@6fps Main stream: 4MP Lite@8fps Sub stream: D1@8fps Main stream: 1080P Lite@12fps Sub stream: D1@12fps Main stream: 720P@12fps Sub stream: D1@12fps
Audio Sample Rate	8KHz,16 bit per channel
Audio Bit Rate	64Kbps per channel
Decoding Capability	XVR301-04G3:Analog: 2 x 5MP Lite@12, 2 x 4MP Lite@15, 2 x 1080P@15 IP: 1 x 4MP@30, 2 x 1080P@30 XVR301-08G3:Analog: 4 x 5MP Lite@6,4x 4MP Lite@8, 4x 1080P Lite @12fps IP: 1 x 4MP@30, 2 x 1080P@30 XVR301-16G3:Analog: 8 x 5MP Lite@6, 8 x 4MP Lite@8, 8 x 1080P Lite@12 IP: 1 x 8MP@30, 2 x 4MP@30, 4 x 1080P@30
Two-way Audio	Description
Two-way Audio	1-ch, RCA(Using the audio input and output)
Analog Snapshot	Description
FTP/Schedule/Event Snapshot	XVR301-04G3:FTP/Event snapshot:4-ch snapshot, up to 704*576 resolution, Schedule snapshot:not supported XVR301-08G3:FTP/Event snapshot:8-ch snapshot, up to 704*576 resolution, Schedule snapshot:not supported XVR301-16G3:FTP/Event snapshot:16-ch snapshot, up to 704*576 resolution, Schedule snapshot:not supported
Network	Description
Incoming Bandwidth	XVR301-04G3:16Mbps (Up to 24Mbps after all analog channel conversion) XVR301-08G3:32Mbps (Up to 40Mbps after all analog channel conversion) XVR301-16G3:40Mbps (up to 56Mbps after all analog camera conversion)
Outgoing Bandwidth	XVR301-04G3:48Mbps XVR301-08G3/XVR301-16G3:64Mbps
Remote Users	128
Protocols	TCP/IP;P2P;UPnP;DHCP;HTTP;HTTPS;DNS;DDNS;SMTP;NTP
Browser(Plugin)	IE(IE10/11) Firefox (version 52.0 and above) Chrome(version 45 and above) Edge(version 79 and above)
Smart	Description

Analog Smart by XVR	Ultra Motion Detection(UMD)
Smart Functions by XVR	XVR301-04G3/XVR301-08G3:4-ch(UMD) XVR301-16G3:8-ch(UMD)
Alarm	Description
General Alarm	Motion
Alert Alarm	IP Conflict;Network Disconnected;Disk offline;Disk Abnormal;Illegal Access;Hard Disk Space Low;Hard Disk Full;Recording/Snapshot Abnormal
Hard Disk	Description
SATA	1 SATA interface
Capacity	Up to 8TB for each HDD (The maximum HDD capacity varies with environment temperature)
External Interface	Description
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface
USB	Rear panel: 2 x USB2.0
Power Supply	DC 12V/2A
Working Environment	Description
Working Temperature	-10°C ~ + 55°C (+14°F ~ +131°F)
Working Humidity	≤ 90% RH(non-condensing)
Power Consumption (without HDD)	XVR301-04G3/XVR301-08G3:≤ 8W XVR301-16G3:≤ 10W
Dimensions	Description
Weight (without HDD)	≤1.1 Kg (2.42lb)
Dimensions	260mm ×226mm× 47mm (10.2" × 8.9"×1.8")
Certification	Description
Certification	CE, FCC, UL, RoHS, WEEE
CE	EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035
FCC	Part15 Subpart B

Daytech.Az