

## Switch NSW2020-10T-POE-IN

NSW2020-10T-POE-IN Unmanaged Ethernet Switch(PoE)

- Multiple working modes to address your business needs: Default(Normal mode), EXTEND(Surveillance mode)
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode
- Support buffer optimization
- All metal housing, safe and reliable

|             |           |
|-------------|-----------|
| Port Number | 10 Port   |
| Port speed  | 100mbp/s  |
| PoE         | PoE       |
| PoE power   | 120 W     |
| Type        | Unmanaged |



## Detailed

|                               |  |
|-------------------------------|--|
| <b>Model</b>                  | <b>NSW2020-10T-POE-IN</b>  |
| <b>Hardware Specification</b> |  |
| Ports Type                    | 10×100Mbps network ports (RJ45), including 8 PoE ports   |
| Prior Ports                   | 1~2  |
| Indicator                     | POWER Steady on: AC input is normal, POWER Off: No AC input, No PoE Indicator, PoE-MAX off: The POE power supply power of the whole machine is less than 80% of the specification, PoE-MAX Steady on : The POE power supply power of the whole machine is greater than 85% of the specification, LINK/ACT Off: No link, LINK/ACT Steady on: Linked, LINK/ACT Flashing: Transmitting data |
| PoE                           | support POE  |

|                        |  |
|------------------------|--|
| Switching capacity     | 2Gbps  |
| Packet Buffer          | 448K bit   |
| Max. PoE Power         | Max capacity: 88W,<br>Max capacity for single port: 30W  |
| Storage Temperature    | -40 °C ~ 70 °C   |
| Working Mode           | Default(Normal mode) : All ports can communicate with each other.,<br>EXTEND(Surveillance mode): Transmission distance up to 250 meters. |
| Power Supply           | DC: 48/51V, powered by adapter (AC100-240V, 50/60Hz)   |
| Max.Power              | 94W  |
| Operating humidity     | 10%~90% (noncondensing)  |
| MAC                    | 1K   |
| Forwarding performance | 1.49Mpps   |
| Cooling Fans           | 0  |
| Weight                 | 0.29KG   |
| Storage humidity       | 5%~90% (noncondensing)   |
| Dimensions (W×D×H)     | 171*103*25mm   |
| Operating temperature  | 0 °C ~ 40 °C (32 °F ~ 104 °F)  |
| Standards              | IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at   |