

Switch NSW2010-6T-POE-IN

NSW2010-6T-POE-IN 4PoE+2Port Switch

- Multiple working modes to address your business needs:Normal, Secure and Surveillance
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode
- Support buffer optimization
- All metal housing, safe and reliable

Port Sayı	6 Port
Port sürəti	100mbp/s
PoE	PoE
PoE gücü	65 W
Tip	Unmanaged



Ətraflı

Model	NSW2010-6T-POE-IN
Ports	6×100Mbps network ports (RJ45),including 4 PoE ports
Standards	IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at
Switching capacity	1.2Gbps
Forwarding performance	0.90Mpps
Packet Buffer	768Kbit
MAC	2K

Dimensions (W×D×H)	160mm x 93mm x 32mm (6.3"×3.7"×1.3")
Weight	<0.6kg
Power supply	AC: 100-240V, 50/60Hz
PoE	802.3at/af
Max. PoE Power	Max capacity: 65W Max capacity for single port: 30W
Cooling Fans	0
Mean Time Between Failure (MTBF)	>50000 hours
Ambient temperature	0°C-45°C (32°F-113°F)
Operating humidity	10%~90% (noncondensing)
Storage humidity	5%~90% (noncondensing)
Indicator	PWR: Steady on: AC input is normal Off: No AC input
	PoE: Off: No PoE power supply Steady on: PoE power supply is normal Flashing: PoE power supply is abnormal
	LINK/ACT: Off: No link Steady: Linked at 10/100Mbps Flashing: Transmitting data
	Speed: Off: Linked at 10/100Mbps On: Linked at 1000Mbps
Working Mode	Default(Normal mode) : All ports can

	communicate with each other. EXTEND(Surveillance mode): Transmission distance up to 250 meters.	
--	---	--