

Switch NSW2020-24T1GT1GC-POE

NSW2020-24T1GT1GC-POE-IN Unmanaged Ethernet Switch(PoE)

- Multiple working modes to address your business needs: Default(Normal mode), VLAN(Secure mode), EXTEND(Surveillance mode)
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode
- Support buffer optimization
- All metal housing, safe and reliable

Port Number	24 Port
Port speed	100mbp/s
PoE	PoE
PoE power	400 W
Type	Unmanaged



Detailed

Model	NSW2020-24T1GT1GC-POE-IN
Hardware Specification	
Ports Type	24×100Mbps PoE ports (RJ45) + 1×1000Mbps Gigaethernet ports +1×1000Mbps Combo ports
Standards	IEEE802.3, IEEE802.3u, IEEE802.3z, IEEE802.3ab, IEEE802.3x, IEEE802.3af, IEEE802.3at, IEEE802.3az
Switching capacity	8.8Gbps
Forwarding performance	6.55Mpps
Packet Buffer	4M bit
MAC	16K

Max. PoE Power	Max capacity: 370W, Max capacity for single port: 30W
PoE	support POE
Prior Ports	1~8
Indicator	POWER Steady on: AC input is normal, POWER Off: No AC input, PoE Off: No PoE power supply, PoE Steady on: PoE power supply is normal, PoE-MAX off: The POE power supply power of the whole machine is less than 80% of the specification, PoE-MAX Steady on : The POE power supply power of the whole machine is greater than 85% of the specification, LINK/ACT Off: No link, LINK/ACT Steady on: Linked, LINK/ACT Flashing: Transmitting data
Power supply	AC: 100-240 V, 50/60 Hz
Max.Power	390W
Storage Temperature	-40 °C ~ 70 °C
Operating temperature	0 °C ~ 40 °C (32 °F ~ 104 °F)
Cooling Fans	1
Mean Time Between Failure (MTB F)	>50000 hours
Dimensions (W×D×H)	440*250*44mm
Weight	2.93KG
Storage humidity	5%~90% (noncondensing)
Operating humidity	10%~90% (noncondensing)
Working Mode	Default(Normal mode) : All ports can communicate with each other., VLAN (Secure mode): Downlink ports can communicate only with uplink ports. Enabling PD keepalive function, the switch will restart the IPC via PoE power when the IPC sends no message in a period of time., Extend(Surveillance mode): Transmission distance up to 250 meters. Downlink ports can communicate only with uplink ports.