

Switch DRL-48V240W1EN

DRL-48V240W1EN Industrial Power Supply Unit 48V, 240W

PoE	PoE
PoE gücü	250 W



Ətraflı

Model	DRL-48V240W1EN
Output	
DC Voltage	48V DC
CONSTANT CURRENT REGIONNote.2	43.2-52.8V DC
RATED CURRENT(forBETypeonly)	5A
RATED POWER	240W
RIPPLE & NOISE (max.) Note.3	< 200mVpp @ 0°C to +70°C < 600mVpp @ -30°C to 0°C

VOLTAGE TOLERANCE Note.4	±1.0%
HOLD UP TIME (Typ.)	20ms typ. @ 115Vac (100% load) 20ms typ. @ 230Vac (100% load)
Environment	
WORKING HUMIDITY	5 to 95% RH (Non-Condensing)
STORAGE TEMP., HUMIDITY	40°C to +85°C
SAFETY& EMC	
SAFETY STANDARDS	IEC 62368-1, IEC 60950-1, IEC 61010-1 & -2-201 EN 62368-1, EN 61010-1 & -2-201 UL 62368-1 GB4943.1 TP TC 004/2011 K60950-1 (24V model only) In conformance with EMC Directive 2014/30/EU and Low Voltage Directive 2014/35/EU
OTHERS	
Dimension	123.6 x 40 x 117.2 mm (4.87 x 1.57 x 4.61 inch)
Packing	0.62 kg (1.37 lb)