

Switch DRL-48V75W1AZ

DRL-48V75W1AZ HIKVISION Industrial (-40°C,+75°C) 75W

- Universal AC input voltage range
- Built-in constant current circuit for reactive loads
- Up to 90% efficiency
- Full power from -10°C to +50°C @ 230Vac with -30°C Cold Start
- Compliance to SEMI F47 @ 200Vac
- Limited Power Source (LPS) certified

PoE	PoE
-----	-----



Ətraflı

Model	DRL-48V75W1AZ
Output	
DC VOLTAGE	48V DC
CONSTANT CURRENT REGIONNote.2	43.2-52.8V DC
RATED CURRENT(forBETypeonly)	1.57A
RATED POWER	75W

RIPPLE & NOISE (max.) Note.3	< 240mVpp @ > -10°C to +70°C < 480mVpp @ ≤ -10°C to -30°C
VOLTAGE TOLERANCE Note.4	±1.0%
HOLD UP TIME (Typ.)	16ms typ. @ 115Vac (100% load) 60ms typ. @ 230Vac (100% load)
Environment	
WORKING HUMIDITY	5 to 95% RH (Non-Condensing)
STORAGE TEMP., HUMIDITY	40°C to +85°C
SAFETY & EMC	
SAFETY STANDARDS	IEC 62368-1, IEC 60950-1, IEC 61010-1 EN 62368-1 UL 62368-1 GB4943.1 TP TC 004/2011 K60950-1 IEC 62368-1 (For DRL-24V75W1AZ & DRL-48V75W1AZ) In conformance with EMC Directive 2014/30/EU and Low Voltage Directive 2014/35/EU
OTHERS	
DIMENSION	123.6 x 27 x 102 mm (4.86 x 1.06 x 4.01 inch)
PACKING	0.22 kg (0.49 lb)