

Switch DS-3E0526P-E/M

DS-3E0526P-E/M 24 Port

- 24 × Gigabit PoE ports, 2 × Gigabit SFP fiber optical ports.
- IEEE 802.3at/af standard.
- IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z standards
- 6 KV surge protection for PoE ports
- PoE power management
- Gigabit network access
- Wire-speed forwarding
- Store-and-forward switching
- Solid high-strength metal shell

Port Number	24 Port
Port speed	100mbp/s
PoE	PoE
PoE power	250 W
Type	Unmanaged



Model	DS-3E0526P-E/M
Power Supply	100-240 VAC, 50/60 Hz, Max. 4 A
Max. Power Consumption	250 W
Power Consumption in Idle	25 W
Installation Mode	Rack (equipped with mounting ears)
Surge Protection	6 KV
Ports	24 × Gigabit PoE port,2 × Gigabit fiber optical port

MAC Address Table	8 K
Switching Capacity	52 Gbps
Packet Forwarding Rate	38.69 Mpps
Internal Cache	4.1 Mbits
PoE Standard	IEEE 802.3af;IEEE 802.3at
PoE Power Pin	End-span: 1/2(+), 3/6(-)
PoE Port	PoE: Ports 1 to 24
Max. Port Power	30 W
PoE Power Budget	225 W
EMC	FCC (47 CFR Part 15, Subpart B),CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020),IC (ICES-003: Issue 7:2020),RCM (AS/NZS CISPR 32: 2015)
Safety	UL (UL 60950-1),CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD (EN 62368-1: 2014+A11: 2017)
Chemistry	CE-RoHS (201165EU); WEEE (201219EU); Reach (Regulation (EC) No.19072006)