

Switch DS-3E0106P-E/M

DS-3E0106P-E/M 4 Port Fast Ethernet Unmanaged POE Switch

- 4 x 10/100Mbps PoE ports, and 2 x 10/100Mbps RJ45 ports.
- IEEE 802.3at/af standard for PoE ports (Max. 35 W PoE output).
- IEEE 802.3, IEEE 802.3u, and IEEE 802.3x standards.
- 6 KV surge protection for PoE ports.
- Up to 300 m long-range transmission.
- Wire-speed forwarding.
- Store-and-forward switching.
- Solid high-strength metal shell.
- Reliable fan-free design.

Port Number	4 Port
Port speed	100mbp/s
PoE	PoE
PoE power	30 W
Type	Unmanaged



Detailed

Model	DS-3E0106P-E/M
Max. Power Consumption	30 W
Power Consumption in Idle	3 W
Surge Protection	6 KV
Ports	4 x 10/100 Mbps PoE port, 2 x 10/100 Mbps RJ45 port
MAC Address Table	2 K

Switching Capacity	1.2 Gbps
Packet Forwarding Rate	0.89 Mpps
PoE Standard	IEEE 802.3af;IEEE 802.3at
PoE Power Pin	8-pin power: 1/2(-), 3/6(+), 4/5(+), 7/8(-)
PoE Port	PoE: Ports 1 to 4
Max. Port Power	30 W
PoE Power Budget	35 W
Long Range	Ports 1 to 4 : up to 300 m. Long range performance may vary depend on camera model or cable condition.
VIP Port	Ports 1 to 2: data on VIP ports is preferentially forwarded when bandwidth resources are insufficient.
EMC	FCC (47 CFR Part 15, Subpart B),CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020),IC (ICES-003: Issue 7:2020),RCM (AS/NZS CISPR 32: 2015)
Safety	UL (UL 60950-1),CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD (EN 62368-1: 2014+A11: 2017)
Chemistry	CE-RoHS (201165EU); WEEE (201219EU); Reach (Regulation (EC) No.19072006)