

Switch DS-3E0310P-E/M

DS-3E0310P-E/M 8 Port Ethernet Unmanaged PoE Switch

- 8 × 10/100 Mbps PoE ports, and 2 × Gigabit RJ45 ports.
- IEEE 802.3at/af standard for PoE ports (Max. 60 W PoE output).
- IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z and IEEE 802.3ab standards.
- 6 KV surge protection for PoE ports.
- Up to 300 m long-range transmission.
- Wire-speed forwarding.
- Store-and-forward switching.
- Solid high-strength metal shell.
- Reliable fan-free design.

Port Number	8 Port
Port speed	100mbp/s
PoE	PoE
PoE power	65 W
Type	Unmanaged



Detailed

Model	DS-3E0310P-E/M
Power Supply	48 VDC, 1.35 A
Max. Power Consumption	65 W
Power Consumption in Idle	5 W
Installation Mode	Desk-Mounted,Wall-Mounted
Surge Protection	6 KV

Ports	8 × 10/100 Mbps PoE port,2 × Gigabit RJ45 port
MAC Address Table	8 K
Switching Capacity	5.6 Gbps
Packet Forwarding Rate	4.17 Mpps
Internal Cache	4 Mbits
PoE Standard	IEEE 802.3af;IEEE 802.3at
PoE Power Pin	8-pin power: 1/2(-), 3/6(+), 4/5(+), 7/8(-)
PoE Port	PoE: Ports 1 to 8
Max. Port Power	30 W
PoE Power Budget	60 W
Long Range	Ports 1 to 8 : up to 300 m. Long range performance may vary depend on camera model or cable condition.
EMC	FCC (47 CFR Part 15, Subpart B),CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020),IC (ICES-003: Issue 7:2020),RCM (AS/NZS CISPR 32: 2015)
Safety	UL (UL 60950-1),CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD (EN 62368-1: 2014+A11: 2017)
Chemistry	CE-RoHS (201165EU); WEEE (201219EU); Reach (Regulation (EC) No.19072006)