

Switch DS-3E0318P-E/M(C)

DS-3E0318P-E/M 16 Port Fast Ethernet Unmanaged PoE Switch

- Intelligent PoE Management When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime
- Up to 300 m Long Range PoE Transmission The distance between IPCs and switch can reach maximum 300 meters
- 6 KV Surge Protection to Improve Reliability in Harsh Environment The built-in surge protection device protects the switch from the sudden lightning surge in harsh environment
- Design for Video Transmission VIP port ensures important data transmission when network congestion occurs

Port Sayı	16 Port
PoE	PoE
PoE gücü	150 W
Tip	Unmanaged



Ətraflı

Model	DS-3E0318P-E/M(C)
Power Supply	100~240 VAC, 50/60 Hz, Max. 2.5 A
Max. Power Consumption	150 W
Max. Power Consumption	20 W
Installation Mode	Desk-Mounted,Wall-Mounted
Surge Protection	6 KV
Ports	16 × 10/100 Mbps PoE port,1× Gigabit RJ45 port,1 × Gigabit combo

MAC Address Table	8 K
Switching Capacity	7.2 Gbps
Packet Forwarding Rate	5.36 Mpps
Internal Cache	4 Mbits
PoE Standard	IEEE 802.3af;IEEE 802.3at
PoE Power Pin	8-pin power: 1/2(-), 3/6(+), 4/5(+), 7/8(-)
PoE Port	PoE: Ports 1 to 16
Max. Port Power	30 W
PoE Power Budget	130 W
Long Range	Ports 9 to 16 : up to 300 m Long range performance may vary depend on camera model or cable condition
EMC	FCC (47 CFR Part 15, Subpart B),CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020),IC (ICES-003: Issue 7:2020),RCM (AS/NZS CISPR 32: 2015)
Safety	UL (UL 60950-1),CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD (EN 62368-1: 2014+A11: 2017)
Chemistry	CE-RoHS (201165EU); WEEE (201219EU); Reach (Regulation (EC) No.19072006)