

Switch DS-3E0326P-E(C)

DS-3E0326P-E(C) 24-Port Fast Ethernet Unmanaged PoE Switch

- Intelligent PoE management
- Up to 300m long-range PoE transmission
- Port isolation to enhance network security
- 6KV surge protection to enhance reliability in harsh environments
- PoE controller to automatically detect and restart unresponsive cameras

Port Number	24 Port
Port speed	100mbp/s
PoE	PoE
PoE power	400 W
Type	Unmanaged



Detailed

Model	DS-3E0326P-E(C)
Power Supply	100~240 VAC, 50/60 Hz, Max. 6.5 A
Max. Power Consumption	400 W
Power Consumption in Idle	30 W
Installation Mode	Rack (equipped with mounting ears)
Surge Protection	6 KV
Ports	24 × 10/100 Mbps PoE port,2 × Gigabit combo
MAC Address Table	16 K
Switching Capacity	8.80 Gbps

Packet Forwarding Rate	6.55 Mpps
Internal Cache	4 Mbits
PoE Standard	IEEE 802.3af;IEEE 802.3at
PoE Power Pin	8-pin power: 1/2(-), 3/6(+), 4/5(+), 7/8(-)
PoE Port	PoE: Ports 1 to 24
Max. Port Power	30 W
PoE Power Budget	370 W
Long Range	Ports 17 to 24: up to 300 m Long range performance may vary depend on camera model or cable condition
Port Isolation	Ports 1 to 24: port isolation mode to improve network security Ports in an isolation group cannot communicate with each other, but they can communicate with ports outside the isolation group
PoE Watchdog	Ports 1 to 24: auto detect and restart the cameras that do not respond
VIP Port	Ports 1 to 8: data on VIP ports is preferentially forwarded when bandwidth resources are insufficient
EMC	FCC (47 CFR Part 15, Subpart B),CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020),IC (ICES-003: Issue 7:2020),RCM (AS/NZS CISPR 32: 2015)
Safety	UL (UL 60950-1),CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD (EN 62368-1: 2014+A11: 2017)
Chemistry	CE-RoHS (2011/65/EU)