

LM32-F200 Monitor

LM32-F200 Monitor

Light and cost-effective plastic housing
 Suitable for continuous 24/7 operation
 178°H/178°V extra-wide viewing angle for overall viewing performance
 High fidelity digital processing for a brilliant and vivid video
 8ms fast response time with no image blurring or ghosting
 Support multiple signal inputs such as HDMI, VGA and USB
 Built-in speakers
 Physical button and infrared remote dual control mode

Size	32"
Display capability	FHD
Panel	IPS



Detailed

Model	LM32-F200
Display	
Screen size	31.5"
Aspect ratio	16:9
Permission	1920×1080 (FHD)
Backlight	LED
Brightness	240 cd/m
Contrast	1400:1

Display color	16.7 MB (8 bit)	
Viewing angle	178°	
Response time	8 ms	
Refresh rate	60 Hz	
Signals		
Entrance	VGA(D-Sub) × 1, HDMI × 1, USB × 1	
Exit	Speaker	8W × 2
Accessories		
Standard	HDMI cable, power cable, remote control, stand	
Additionally	Hanging bracket	
Certificates		
Certificates	CE/FCC	
Environment		
Operating temperature	0°C ~ 40°C (32°F ~ 104°F)	
Working humidity	10% ~ 85%	
Electrical properties		
Power supply	100~240VAC (+/- 10%), 50/60Hz	
Power Consumption (Standard)	55 W	
Power Consumption (Standby)	≤0.5 W	
General information		
Type	Interior	
Bezel width	13.9 mm (U/R/L), 20.5 mm (B)	
Wall mount	75 x 75 mm (3.0" x 3.0")	

Sizes without standard	731.4 × 432.6 × 67.5 mm (28.8" × 17" × 2.7")
Net weight	3.9 kg (8.6 lbs)
Gross weight	5.1 kg (11.2 lbs)

Daytech.Az