

Monitor LM43-F200

Light and cost-effective plastic housing  
suitable for continuous 24/7 operation  
178°H/178°V extra-wide viewing angle for overall viewing performance  
High fidelity digital processing for a brilliant and vivid video  
8ms fast response time with no image blurring or ghosting  
Support multiple signal inputs such as HDMI, VGA and USB  
Built-in speakers  
Physical button and infrared remote dual control mode  
Low energy consumption, long service life

Size	43"
Display capability	FHD
Panel	IPS



Detailed

Model	LM43-F200
Display	
Screen size	42.5"
Aspect ratio	16:9
Permission	1920×1080 (FHD)
Backlight compensation	LED
Brightness / Lighting	330 cd/m
Contrast	1200:1

Display color	16.7 MB (8 bit)	
Viewing angle	178° / 178°	
Response time	8 ms	
Refresh rate	60 Hz	
Signal		
Entrance	VGA (D-Sub) × 1, HDMI × 1, USB × 1	
Exit	Speaker	4 V x 2
Additional properties		
Type	Interior	
Accessories		
Standard	HDMI cable, power cable, remote control, stand	
Additionally	Hanging bracket	
Certificates		
Certificates	CE/FCC	
Environment		
Operating temperature	0°C ~ 40°C (32°F ~ 104°F)	
Working humidity	20% ~ 85%	
Electrical properties		
Power supply	AC100 ~ 240V (+/- 10%), 50 / 60 Hz	
Power Consumption (Standard)	75 W	
Power Consumption (Standby)	≤0.5 W	
General information		
Dimensions	969.1 × 566.8 × 82.4mm (38.2" × 22.3" × 3.2")	
Wall mount	400 x 200 mm (15.8" x 7.9")	

Net weight	7.4 kg (16.3 lbs)
Gross weight	9.5 kg (20.94 lbs)