

DS-2CD2123G0-IS

DS-2CD2123G0-IS 2,8mm 2mp IR30m Dome IP KAMERA HIKVISION

Növ	IP
Megapixel	2 MP
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma	İR
İşıqlandırma məsafəsi	30 m
Mikrofon	Mic
Qoruma	IP67
Material	Metal



Ətraflı

Model	DS-2CD2123G0-IS
Matrix	Color: 0.01lx@(F1.2,AGC on) B/W: 0.028lx@(F2.0,AGC on), 0lx with IR
Electronic shutter speed	1/3s ~ 1/100,000s, support slow shutter
Lens	2.8mm@F2.0
Lens mount	M12
Lens viewing angle	2.8mm: horizontal: 114°, vertical: 62°, diagonal: 135°
Day/Night mode	Mechanical IR filter
Video compression	Main stream: H.265/H.264 Additional stream: H.265/H.264/MJPEG Third stream: H.265/H.264
H.264 profile	Main Profile/High Profile
H.265 profie	Main Profile
Video bitrate	32 kbit/s-16 Mbit/s
Audio compression	G.711/G.722.1/G.726/MP2L2/PCM
Audio bitrate	64kbps(G.711) / 16kbps(G.722.1) / 16kbps(G.726) /

	32-192kbps(MP2L2)
Maximum resolution	1920×1080
Main thread	25 fps (1920 × 1080, 1280 × 960, 1280 × 720)
Additional stream	25 fps (640 × 360, 352 × 288)
Third stream	25 fps (1280×720, 640×360, 352×288)
S.V.C.	Supported
Image Settings	Saturation, brightness, contrast, sharpness, corridor mode, mirroring and privacy mask are adjustable via client software or web browser
Image enhancement	120dB WDR, 3D DNR, BLC, 1 ROI region per stream
Day/Night switching	Auto/schedule/alarm
Motion detection	Detection of line crossing, area intrusion
Object recognition	Face detection
Network storage	NAS (NFS,SMB/CIFS support), ANR
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Alarm Triggered	Smart functions, network interruption, IP address conflict, authorization errors, storage errors
Alarm Actions	Notifying the client, sending email, uploading to FTP, activating the recording channel
Client	iVMS-4200, Hik-Connect, iVMS-5200
Web browser	IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+
Network interface	1 RJ45 10M/100M Ethernet
Audio input	1 input (line, microphone)
Audio output	1 audio output (mono audio)
Alarm Interfaces	1 input / 1 output
Environmental noise filtering	Supported
Sampling frequency	8kHz/ 16kHz/ 32 kHz/ 44.1 kHz/ 48 kHz
Local storage	Slot for microSD/SDHC/SDXC up to 128GB
Nutrition	DC12V±25%/PoE(802.3af)
Power consumption	7.5W max.
Working conditions	-40 °C...+60 °C, humidity 95% or less (non-condensing)
Color	White black
Protection	IP67, IK10, TVS 2000V transient voltage suppressor for

	lightning protection
IR Illumination Range	Up to 30 m
Material	Metal
Dimensions	Ø111 × 82.4mm
Weight	0.61 kg