

Micro SD TF-P100/64GB

TF-P100/64GB P100 microSD Memory Card

High-quality memory, precise manufacturing, strict inspection ensure high speed and stable performance  
High compatibility can meet various user needs when using digital products, such as watching movies, playing games, recording videos, listening to music, and sending files  
High-speed transmission of up to 100MB/s; write speed is up to 90MB/s  
Four types of protection: High and low temperature resistant, water proof, anti-magnetic, and anti X-ray; adapt to a variety of environments

|             |       |
|-------------|-------|
| Memory size | 64 GB |
|-------------|-------|



Detailed

| Model                 | TF-P100/64GB   |
|-----------------------|----------------|
| Basic information     |                |
| Capacity              | 64 GB          |
| Manufacturing process | TLC            |
| Reading speed         | Up to 100 Mbps |
| Write speed           | Up to 38 Mbps  |
| Recording frequency   | C10/U3/V30/A2  |
| UHS                   | UHS-I          |
| P/E                   | 1000           |

|                            |                                                                                                                                              |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| File system                | exFAT                                                                                                                                        |
| Compatibility              | CCTV/Security Cameras, Hi-Fi Players, Tablets, Car DVRs, Sports Cameras, Digital Stereos, Mobile Handheld Terminals, Digital Video Recorders |
| Personalization            | Data encryption, life warning, health detection (used with certain Dahua cameras)                                                            |
| <b>Protection</b>          |                                                                                                                                              |
| Four types of protection   | Resistance to high and low temperatures, Waterproof, Anti-magnetic and X-ray proof                                                           |
| <b>Environment</b>         |                                                                                                                                              |
| Operating temperature      | 0°C to 70°C (32°F to 158°F)                                                                                                                  |
| Storage temperature        | -25°C to 85°C (-13°F to 185°F)                                                                                                               |
| Working humidity           | From 5% to 95% (non-condensing)                                                                                                              |
| <b>General information</b> |                                                                                                                                              |
| Dimensions                 | 15mm x 11mm x 1.0mm (0.59" x 0.43" x 0.04")                                                                                                  |
| Net weight                 | 0.33 g                                                                                                                                       |
| Gross weight               | 11.3 g                                                                                                                                       |