

## Switch DS-3E1510P-SI

DS-3E1510P-SI 10p 2x GB SFP Gigabit Smart Managed POE Switch Hikvision

- 8 × gigabit PoE ports, and 2 × gigabit fiber optical ports
- IEEE 802.3at/af standard for PoE ports
- 6 KV surge protection for PoE ports
- AF/AT camera can reach up to 300 m in extend mode
- PoE watchdog to auto detect and restart the cameras that do not respond
- Various layer 2 management protocols such as STP/RSTP, VLAN, link aggregation, SNMP, QoS and so on

|             |           |
|-------------|-----------|
| Port Sayı   | 8 Port    |
| Port sürəti | 1000mbp/s |
| PoE         | PoE       |
| PoE gücü    | 120 W     |
| Tip         | Managed   |



## Ətraflı

|                           |  |
|---------------------------|--|
| <b>Model</b>              | <b>DS-3E1510P-SI</b>                                 |
| Shell                     | Metal material                                       |
| Power Supply              | 48 VDC, 2.5 A  |
| Installation Mode         | Desk-Mounted, Wall-Mounted                           |
| Max. Power Consumption    | 120 W  |
| Power Consumption in Idle | 7 W  |
| Surge Protection          | 6 KV   |
| Ports                     | 8 × Gigabit PoE port, 2 × Gigabit fiber optical port |
| MAC Address Table         | 8 K  |

|                        |  |
|------------------------|--|
| Switching Capacity     | 20 Gbps  |
| Packet Forwarding Rate | 14.88 Mpps   |
| Internal Cache         | 4.1 Mbits  |
| PoE Standard           | IEEE 802.3af, IEEE 802.3at   |
| PoE Power Pin          | End-span: 1/2(+), 3/6(-)   |
| PoE Port               | PoE: Ports 1 to 8  |
| Max. Port Power        | 30 W   |
| PoE Power Budget       | 110 W  |
| Long Range             | <p>Ports 1 to 8: up to 300 m</p> <p>Long range performance may vary depend on camera model or cable condition</p>  |
| Port Isolation         | <p>Ports 1 to 8: port isolation mode to improve network security</p> <p>Ports in an isolation group cannot communicate with each other, but they can communicate with ports outside the isolation group.</p>   |
| PoE Watchdog           | Ports 1 to 8: auto detect and restart the cameras that do not respond  |
| HPP                    | <p>Support one-click activation and remote management via Hik-Partner Pro. Functions supported:</p> <ol style="list-style-type: none"> <li>1. Display the port rate</li> <li>2. Display the port bandwidth utilization rate</li> <li>3. Display the PoE power usage</li> <li>4. Display topology information</li> <li>5. Display the alarm status</li> <li>6. Restart ports and devices</li> <li>7. Enable port long-range mode</li> <li>8. Remotely upgrade the device</li> </ol> |
| System Maintenance     | Remote upgrade, default parameters recovery, logs viewing, basic network parameters configuration, import and export configuration, time sync  |
| EMC                    | <p>FCC (47 CFR Part 15, Subpart B);</p> <p>CE-EMC (EN 55032: 2015, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011 +A1: 2014, EN 55035: 2017);</p> <p>IC (ICES-003: Issue 6);</p> <p>RCM (ASNZS CISPR 32: 2015)</p>  |
| Safety                 | <p>UL (UL 60950-1);</p> <p>CB (IEC 60950-1:2005, AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition);</p>   |

|           |  |
|-----------|--|
|           | CE-LVD (EN 60950-1: 2006 + A11: 2009 +A1: 2010+A12: 2011+A2: 2013, EN 62368-1: 2014+A11: 2017) |
| Chemistry | CE-RoHS (201165EU);<br>WEEE (201219EU);<br>Reach (Regulation (EC) No.19072006)                 |

---

[Daytech.Az](http://Daytech.Az)