

Switch DS-3E1510P-SI

DS-3E1510P-SI 10p 2x GB SFP Gigabit Smart Managed POE Switch Hikvision

- 8 × gigabit PoE ports, and 2 × gigabit fiber optical ports
- IEEE 802.3at/af standard for PoE ports
- 6 KV surge protection for PoE ports
- AF/AT camera can reach up to 300 m in extend mode
- PoE watchdog to auto detect and restart the cameras that do not respond
- Various layer 2 management protocols such as STP/RSTP, VLAN, link aggregation, SNMP, QoS and so on

Port Number	8 Port
Port speed	1000mbp/s
PoE	PoE
PoE power	120 W
Type	Managed



Detailed

Model	DS-3E1510P-SI
Shell	Metal material
Power Supply	48 VDC, 2.5 A
Installation Mode	Desk-Mounted,Wall-Mounted
Max. Power Consumption	120 W
Power Consumption in Idle	7 W
Surge Protection	6 KV
Ports	8 × Gigabit PoE port,2 × Gigabit fiber optical port
MAC Address Table	8 K

Switching Capacity	20 Gbps
Packet Forwarding Rate	14.88 Mpps
Internal Cache	4.1 Mbits
PoE Standard	IEEE 802.3af,IEEE 802.3at
PoE Power Pin	End-span: 1/2(+), 3/6(-)
PoE Port	PoE: Ports 1 to 8
Max. Port Power	30 W
PoE Power Budget	110 W
Long Range	Ports 1 to 8: up to 300 m Long range performance may vary depend on camera model or cable condition
Port Isolation	Ports 1 to 8: port isolation mode to improve network security Ports in an isolation group cannot communicate with each other, but they can communicate with ports outside the isolation group.
PoE Watchdog	Ports 1 to 8: auto detect and restart the cameras that do not respond
HPP	Support one-click activation and remote management via Hik-Partner Pro. Functions supported: 1. Display the port rate 2. Display the port bandwidth utilization rate 3. Display the PoE power usage 4. Display topology information 5. Display the alarm status 6. Restart ports and devices 7. Enable port long-range mode 8. Remotely upgrade the device
System Maintenance	Remote upgrade, default parameters recovery, logs viewing, basic network parameters configuration, import and export configuration, time sync
EMC	FCC (47 CFR Part 15, Subpart B); CE-EMC (EN 55032: 2015, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011 +A1: 2014, EN 55035: 2017); IC (ICES-003: Issue 6); RCM (ASNZS CISPR 32: 2015)
Safety	UL (UL 60950-1); CB (IEC 60950-1:2005, AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition);

	CE-LVD (EN 60950-1: 2006 + A11: 2009 +A1: 2010+A12: 2011+A2: 2013, EN 62368-1: 2014+A11: 2017)
Chemistry	CE-RoHS (201165EU); WEEE (201219EU); Reach (Regulation (EC) No.19072006)