

Switch DS-3E0526P-E

DS-3E0526P-E 24 Port Gigabit Unmanaged PoE Switch

Layer 2 network switch designed for video data transmission
24 x 10/100/1000 Mbps ethernet port, 1 x 10/100/1000 Mbps uplink ethernet port and 1 x 10/100/1000 Mbps uplink SFP port
IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z network standards available
IEEE 802.3 af & at high PoE power supply
Store-and-forward switching
Safe and reliable using 6 KV high surge protection
Plug and play ensures simplicity and convenience

Port Number	24 Port
Port speed	100mbp/s
PoE	PoE
PoE power	400 W
Type	Unmanaged



Detailed

Model	DS-3E0526P-E
Shell	Metal Material
Power Supply	100~240 VAC, 50/60 Hz, Max. 6.5 A
Max. Power Consumption	400 W
Power Consumption in Idle	30 W
Installation Mode	Desk-Mounted,Rack (equipped with mounting ears)
Surge Protection	6 KV
Ports	24 × Gigabit PoE port;1 × Gigabit RJ45 port;1 × Gigabit fiber optical port
MAC Address Table	8 K
Switching Capacity	52 Gbps

Packet Forwarding Rate	38.69 Mpps
Internal Cache	4.1 Mbits
PoE Standard	IEEE 802.3af,IEEE 802.3at
PoE Power Pin	End-span: 1/2(+), 3/6(-)
PoE Port	PoE: Ports 1 to 24
Max. Port Power	30 W
PoE Power Budget	370 W
EMC	FCC (47 CFR Part 15, Subpart B),CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020),IC (ICES-003: Issue 7:2020),RCM (AS/NZS CISPR 32: 2015)
Safety	UL (UL 60950-1),CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD (EN 62368-1: 2014+A11: 2017)
Chemistry	CE-RoHS (2011/65/EU)