

Switch DS-3E2528P

DS-3E2528P HIKVISION L2 managed POE+ switch 24 ports + 4 Uplink gigabit SFP ports, POE budget 380W

24 Gigabit Poe electrical ports and 4 Gigabit combo ports.

Support static routing, policy routing, rip, OSPF and other three-layer routing protocols.

IGMP snooping and GRMP for filtering multicast traffic.

Port-based VLAN, IEEE 802.1Q VLAN, and GVRP to ease network planning.

Support IEEE 802.1x authentication, radius and bdtacacs + authentication.

Support EAPs and ERPs Ethernet ring network protection protocol.

QoS (IEEE 802.1P/1Q and TOS/DiffServ) to increase determinism.

Support IEEE 802.3af/at compliant PoE.

Each PoE port provides up to 30W output power.

PoE management: PoE device detection, PoE power management.

Easy network management by web browser, Console, Telnet, SSH.

SNMPv1/v2c/v3 for different levels of network management.

Port Number	24 Port
Port speed	1000mbp/s
PoE	PoE+
PoE power	400 W
Type	Managed



Detailed

Model	DS-3E2528P
Dimensions	440.00 mm x 44.00 mm x 210.00 mm
Operating Humidity	10% to 90% (no condensation)
Power Supply	100-240 VAC, 50/60 Hz
Power Consumption	17 W
MAC Address Table	8 K

Ports	24 × 1 Gigabit PoE port, 4 × 1 Gigabit combo	
Switching Capacity	Whole-Device Performance: 56 Gbps Port Performance: 56 Gbps	
Packet Forwarding Rate	Whole-Device Performance: 41.66 Mpps Port Performance: 41.66 Mpps	
PoE Standard	IEEE 802.3af, IEEE 802.3at	
PoE Power Pin	1/2 (+), 3/6 (-)	
PoE Power Budget	370 W	
VLAN	Support IEEE 802.1Q (VLAN), 4096 VLAN IDs Support GVRP Support QinQ Support VLAN based on MAC/protocol/IP subnet/policy/port Support Private VLAN Support 1:1 and N:1 VLAN mapping functions	
QoS	Support Diff-Serv QoS Support 802.1p/DSCP priority mapping Support queue scheduling including SP, WRR, WFQ, SP+WRR, SP+WFQ Support priority marking and remarking Support traffic shaping Support congestion avoidance, Tail-Drop and WRED Support 802.1p, TOS, DSCP, and EXP priority mapping Support port/flow-based rate limiting	
Management Method	Support Console, Telnet, SSH Support web, http, https Support FTP, TFTP, Xmodem, SFTP Support SNMP V1/V2c/V3 Support RMON Support NTP	
Multicast	Support IGMP v1/v2/v3 Snooping Support IGMP V1/V2/V3 Support MLD Snooping v1/v2 Support MLD v1/v2	
Security	Support AAA, TACACS+, Radius authentication Support 802.1X authentication, MAC authentication,	

	<p>MAC bypass authentication</p> <p>Support to prevent DOS, ARP attack function, ICMP anti attack</p> <p>Support binding of IP, MAC, port and VLAN</p> <p>Support MAC authentication</p> <p>Support MAC address filtering</p> <p>Support broadcast/multicast/unknown-unicast storm control</p>
EMC	FCC (ANSI C63.4, 47 CFR PART 15B); CE-EMC/RCM (EN 55032: 2015+A11:2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1:2019, EN 50130-4:2011+A1:2014, EN 55035:2017+A11:2020); IC (ICES-003: Issue 24)
Safety	UL (UL 62368-1); CB/RCM (IEC 62368-1:2014); CE-LVD (EN 62368-1:2014+A11:2034)
Chemistry	CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2023)