

Switch DS-3E1326P-EI

DS-3E1326P-EI 24 Port Fast Ethernet Smart POE Switch

- 24 × 10/100M PoE ports, 2 × Gigabit combos.
- Total PoE Power Budget 370 W
- Support 802.1Q VLAN
- Support PoE watchdog to detect and restart the cameras that do not respond
- Support STP/RSTP Loop prevention
- Up to 300 m Long Range PoE Transmission
- 6 kV Surge Protection

Port Number	24 Port
Port speed	100mbp/s
PoE	PoE
PoE power	400 W
Type	Unmanaged



Detailed

Model	DS-3E1326P-EI
General	
Shell	Metal Material
Net Weight	2.83 kg (6.24 lb)
Gross Weight	3.8 kg (8.38 lb)
Dimensions	440.00 mm x 44.00 mm x 220.80 mm
Operating Temperature	0 °C to 45 °C (32 °F to 113 °F)

Storage Temperature	-40 °C to 85 °C (-40 °F to 185 °F)
Operating Humidity	5% to 95% (no condensation)
Relative Humidity	5% to 95% (no condensation)
Power Supply	100~240 VAC, 50/60 Hz, Max. 6.3 A
Max. Power Consumption	400 W
Power Consumption in Idle	30 W
Surge Protection	6 KV
Network Parameters	
Ports	24 × 10/100 Mbps PoE port,2 × Gigabit combo
MAC Address Table	16 K
Internal Cache	4 Mbits
PoE Power Supply	
PoE Standard	IEEE 802.3af;IEEE 802.3at
PoE Power Pin	8-pin power: 1/2(-), 3/6(+), 4/5(+), 7/8(-)
PoE Port	PoE: Ports 1 to 24
Max. Port Power	30 W
PoE Power Budget	370 W
Approval	
EMC	CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020),IC (ICES-003: Issue 7:2020),RCM (AS/NZS CISPR 32: 2015)
Safety	CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition)), CE-LVD (EN 62368-1: 2014+A11: 2017)
Chemistry	CE-RoHS (2011/65/EU),WEEE (2012/19/EU),Reach (Regulation (EC) No.1907/2006)

