

Switch DS-3E0524TF

DS-3E0524TF 24 Port Gigabit Unmanaged Switch

Layer 2 network switch designed for video data transmission
12 x 10/100/1000 Mbps ethernet ports and 12 x 10/100/1000 Mbps SFP ports
IEEE 802.3, IEEE802.3u and IEEE802.3x network standards available
Store-and-forward switching
Delay of data-exchange less than 5us
Safe and reliable using 4 KV high surge protection
Plug and play ensures simplicity and convenience

Port Number	24 Port
Port speed	100mbp/s
PoE power	30 W
Type	Unmanaged



Detailed

Model	DS-3E0524TF
Dimensions	440.00 mm x 44.50 mm x 186.50 mm
Shell	Metal Material
Power Supply	220 VAC
Power Consumption	≤ 30 W
Ports	12 × Gigabit RJ45 ports, and 12 × Gigabit fiber optical ports
Port Type	Electrical ports: RJ45, Full/half duplex, MDI/MDI-X self-adptive,Fiber optical port: SFP packaging
Standard	IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3x
MAC Address Table	16 K
Switching Capacity	48 Gbps

Packet Forwarding Rate	35.7 Mpps
Internal Cache	12 Mbit
EMC	FCC (ANSI C63.4, 47 CFR PART 15B); CE-EMC/RCM (EN 55032: 2015+A11:2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1:2019, EN 50130-4:2011+A1:2014, EN 55035:2017+A11:2020); IC (ICES-003: Issue 14)
Safety	UL (UL 62368-1); CB/RCM (IEC 62368-1:2014); CE-LVD (EN 62368-1:2014+A11:2024)
Chemistry	CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2013)