

Router TL-MR3020

TP-LINK TL-MR3020 3G/4G WIRELESS N ROUTER

Shared 3G/4G mobile connectivity *, compatible with more than 120 UMTS/HSPA/EVDO 3G USB modem models

Wireless connection speed up to 300 Mbps

Three operating modes: 3G / 4G router*, Client router (WISP)

Wi-Fi	3G/4G
-------	-------



Detailed

Model	TL-MR3020
Hardware Specifications	
Interfaces	1 10/100 Mbps WAN/LAN port, USB 2.0 port for 3G/4G modems, Mini-USB port for power supply
Buttons	WPS/Reset button, mode switch
External power supply	5V, 1A
Dimensions (W x L x H)	74 x 67 x 22 mm
Type and / or number of antennas	Built-in
Wi-Fi Settings	
Wi-Fi Standards	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Frequency Ranges	2400-2483. 5 MHz

EEIM	< 20 dBm or < 100 MW
Operating Modes	3G Router, Portable Access Point (AP), WISP Client router
Wi-Fi network Protection	Supports 64/128-bit WEP, WPA-PSK/WPA2-PSK encryption, and wireless MAC address filtering
Software Features	
Safety	Firewall, MAC address filtering, protection against DoS attacks
DHCP	Server, list of DHCP clients, address reservation
Port Forwarding	Virtual Server, Port Triggering, DMZ, UPnP
Access Control	Parental control, Node list, Scheduled access, Rule management
Other	
Certification Process	CE, FCC, RoHS
Environmental parameters	Operating temperature:-10°C~60°C Storage temperature: -40°C~80°C Relative humidity of the air during operation: 10%~90%, non-condensing Storage relative humidity: 5%~90%, non-condensing