

Mikrafon D7322 Delegate

D7322 Mikrafonlar Delegate

D7322 is a delegate microphone, location is not limited, support registration function. Using low latency technology, the minimum latency is less than 20ms and uncompressed audio transmission. With 48K sampling rate, digital control, high-quality audio transmission.
New generation 5G Wi-Fi all-digital wireless conference system, instant setup, leaves more time for minds to inspire.



Ətraflı

Model		D7322
The structure type		Embedded
Effective frequency range of gain limitation (± 3dB)	Unit A to Unit B.	130Hz-14kHz
	Host to unit line	130Hz-14kHz
	Unit to host line output	50Hz-14kHz
Speaker power		1.2W
Static power consumption		<3.2W
Maximum power consumption:		4.5W
Signal-to-noise ratio		>81dB
Crosstalk attenuation		>80dB
Harmonic distortion		<1%
Headphone output		9dBu, 8-32 Ω, 3.5mm
Operating Power Supply(Battery Pack)		DC5V is charged by Type-C port (more efficient charging in off state)

Microphone type		Elector cardiac capacitive type
	Sensitivity	-30dBV/pa
	input resistance	2kΩ
	Equivalent noise	20dB(SPL)
	Maximum sound pressure level	125dB(THD<3%)
Package dimensions:		485×280×120mm (with two in a bpx)
Machine Dimensions (W × D × H)		175×133×46mm
Gross weight		2.0kg
Net weight		0.6kg