

DS-D5022F2-1V2S Monitor

DS-D5022F2-1V2S 22" MONITOR HIKVISION

- 100 Hz refresh rate, more fluid and life-like video
- Ultra-thin device body with ultra-thin border for 3 sides
- 8 bit LVDS FHD (1920 × 1080) display
- Low blue light design for eye care
- Multiple interfaces, including VGA, HDMI, audio out, and built-in speaker
- Support VESA wall mount

Ölçü	22"
Görüntü imkanı	FHD
Tezlik	100 Hz



Ətraflı

Display	
Screen Size	22-inch
Active Display Area	478.656 (H) mm × 260.280 (V) mm
Resolution	1920x1080
Backlight	E-LED
Pixel Pitch	0.241 mm (H) × 0.241 mm (V)
Brightness	250 cd/m²

Viewing Angle	178° (H) / 178° (V)
Color Depth	8 bit ,16.7 M
Contrast Ratio	4000 : 1
Response Time	8ms
Refresh Rate	Max. 100Hz , Typ. 60 Hz
Haze	Haze 25%, 3H
Reliability	7 × 24 H
Color Gamut	72% NTSC
Interface	
Video & Audio Input	HDMI 1.4 × 1, VGA × 1□Audio In × 1
Video & Audio Output	Speaker × 2 (4Ω 2W)
Power	
Power Supply	DC 12V, 2.0A
Power Consumption	≤ 24 W
Standby Consumption	≤ 0.5 W
Working Environment	
Working Temperature	0°C to 40 °C (32 °F to 104 °F)
Working Humidity	20% to 90% RH (Non-Condensing)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Storage Humidity	10% to 90% RH (Non-Condensing)
Casing Material	Plastic