

Access Point RM2-TI 2,4 GHz

Ubiquiti 2.4GHz Rocket MIMO Airmax Titanium RM2-TI

WiFi standard 2.4 GHz

Operating range 2412-2462MHz

Network interface 2 GbE



Detailed

Technical specifications	
Processor	Atheros MIPS 24KC, 400 MHz
Random access memory	32 MB SDRAM, 8MB Flash
Network interface	2x10 / 100 BASE-TX (cat. 5, RJ-45), Ethernet interface
Transmitter power	600 MW
Channel width	5/10/20/40 MHz
Operating range:	2412-2462 MHz (802.11 b/g / n)
Coverage area	More than 50 km with external placement
Software	AirOS
Sizes	160 x 80 x 30 mm
Weight	0.5 kg
Housing material	UV - resistant plastic for outdoor use
Maximum power consumption	6.5 W
Power unit	24 V, 1 A. Supplied with an injector.
Power supply method	PoE. Voltage is supplied via Ethernet (pair 4 and 5 - positive, 7 and 8 - negative)
Operating temperature	-30 to +75 Seconds
Humidity	5 to 95% (with condensation)
Vibration tests	ETSI300-019-1.4

Certificate of Conformity	FCC 15.247, IC, CE
Antenna	Absent
External antenna connector	2 x RPSMA (Waterproof)