

Kabel CCTV Mini U/4 (Cu/Al)

Recher Cable CCTV 1+4 hf Mini U 4 Cu Al 4x0.22 500m

Kabelin Tipi	1+4
Metr	500m



Ətraflı

Operating temperature	-30 °C ... +70 °C
Bending radius min.	10 x D
Impedance	75 ± 3 Ω
Capacitance	54 ± 2 pF/m
Velocity of propagation	%83 ± 2
Insulation resistance min.	2 G Ω x km
Operating voltage max.	1000 V
Test voltage	2500 V
Standards	EN 50117, IEC 61196
Fire performans	Vertical flame propagation EN 60332-1-2
Satellite distribution2)	2150MHz - 40m
VHF/UHF distribution3)	860MHz - 100m
S-band Cable TV distributio	470MHz - 140m
Attenuation @20°C max	50 MHz 7,26 dB/100m 200 MHz 14,23 dB/100m 470 MHz 21,91 dB/100m 860 MHz 29,96 dB/100m 1000 MHz 32,43 dB/100m 2150 MHz 48,82 dB/100m 2400 MHz 51,83 dB/100m 3000 MHz 58,59 dB/100m
Return Loss	5-470 MHz > 20dB 470-1000MHz > 18 dB 1000-2000 MHz > 16 dB

	2000-3000 MHz > 15 dB	
--	-----------------------	--

Daytech.Az