

Router AX1800

TP-LINK AX1800 WI-FI 6 ROUTER ARCHER AX23 EU

Wi-Fi speeds up to 1.8 Gbps - enjoy smooth streaming, downloading files and online gaming without lag or buffering
 Multiple connections at once — Wi-Fi 6 lets you send more data to more devices with OFDMA and MU-MIMO technologies while reducing latency
 Wide Wi-Fi coverage area - thanks to an improved algorithm, Beamforming technology and high-performance antennas
 Latest chipset - High-efficiency chipset provides stable and fast Wi-Fi with lower power consumption
 Parental Control - Powerful free parental control lets you block URLs, manage profiles, pause internet connections, and more
 Works with most ISPs - L2TP/PPTP and IPTV support
 Easy setup - Set up your router in minutes with the TP-Link Tether app
 Backward compatibility - supports all previous 802.11 Wi-Fi standards



Detailed

Wireless broadcasting	
Standards	Wi-Fi 6 5 GHz - IEEE 802.11ax/ac/n/a 2.4 GHz - IEEE 802.11ax/n/b/g
Wi-Fi speed	AX1800 5GHz: Up to 1201Mbps (802.11ax) 2.4GHz: Up to 574Mbps (802.11ax)
Wi-Fi coverage	For three-room apartments 4 Fixed Antennas Multiple antennas form a strong signal to extend the range Beamforming Concentrates the wireless signal towards clients to extend the range of Wi-Fi
Wi-Fi Bandwidth	Tall Dual Band

	<p>Assign each device its own band for optimal performance</p> <p>OFDMA Simultaneously communicate with multiple Wi-Fi 6 clients</p> <p>MU-MIMO Simultaneously communicate with multiple MU-MIMO clients</p> <p>Airtime Fairness Improve network efficiency by ensuring equal transmission time for all clients</p> <p>4 Streams Increased throughput for your devices</p>
Operating modes	<p>Router</p> <p>Access Point</p>

HARDWARE	
CPU	Dual-core processor
Ethernet ports	<p>1 Gigabit WAN port</p> <p>4 Gigabit LAN ports</p>
Buttons	<p>WPS/Wi-Fi</p> <p>Power (Power On/Off)</p> <p>Reset (Reset settings)</p>
Nutrition	12 V □ 1 A

Safety	
Wi-Fi encryption	<p>WPA</p> <p>WPA2</p> <p>WPA3</p> <p>WPA/WPA2-Enterprise (802.1x)</p>
Network security	<p>SPI Firewall</p> <p>Access Control</p> <p>IP and MAC Binding</p> <p>Application Layer Gateway</p>
Guest network	5 GHz and 2.4 GHz
VPN Server	<p>OpenVPN</p> <p>PPTP</p>

Software Features	
Protocols	<p>IPv4</p> <p>IPv6</p>
OneMesh™	<p>OneMesh™ Support</p> <p>OneMesh™ enables you to create a more flexible whole-home network with TP-Link OneMesh™ devices without having to replace your current devices or purchase a new Wi-Fi ecosystem</p>
Parental control	<p>URL Filtering</p> <p>Control Time Spent Online</p>
WAN Types	<p>Dynamic IP</p> <p>Static IP</p> <p>PPPoE</p> <p>PPTP</p> <p>L2TP</p>
Prioritization (QoS)	Device prioritization
Cloud service	<p>Auto Firmware Update</p> <p>Over-the-Air Firmware Update</p> <p>TP-Link ID</p>

	DDNS
NAT Forwarding	Port Forwarding Launching DMZ UPnP Ports
IPTV	IGMP Proxy IGMP Snooping Bridge VLAN Tagging
DHCP	Address Reservation Client List DHCP Server
DDNS	TP-Link NO-IP DynDNS

PHYSICAL PARAMETERS	
Dimensions (W x D x H)	260.2 x 135.0 x 38.6 mm
Delivery set	Wi-Fi router Archer AX23 Power adapter Ethernet cable RJ45 Quick setup guide

OTHER	
System requirements	Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+ or another browser that supports JavaScript Cable or DSL modem (if necessary) Subscription to an Internet service provider (for Internet access)
Certification	FCC, CE, RoHS
Environment	Operating temperature: 0...+40 °C Storage temperature: -40...+70°C Operating humidity: 10-90% non-condensing Storage humidity: 5-90% non-condensing

TEST RESULTS	
Wi-Fi transmitter power	< 20 dBm or < 100 mW
Wi-Fi Receiver Sensitivity	5GHz 11a 6Mbps: -96dBm 11a 54Mbps: -75dBm 11ac VHT20_MCS0: -95dBm 11ac VHT20_MCS8 : -71dBm 11ac VHT40_MCS0: -92dBm 11ac VHT40_MCS9: -66dBm 11ac VHT80_MCS0: -89dBm 11ac VHT80_MCS9: -62dBm 11ax HE20_MCS0 : -95dBm 11ax HE20_MCS11: -64dBm 11ax HE40_MCS0: -92dBm 11ax HE40_MCS11: -60dBm 11ax HE80_MCS0: -89 dBm 11ax HE80_MCS11: -59 dBm 2.4 GHz 11g 6 Mbps: -96 dBm 11g 54 Mbps: -75 dBm 11n HT20_MCS0 : -95 dBm 11n HT20_MCS7: -75 dBm 11n HT40_MCS0: -92 dBm 11n HT40_MCS7: -72 dBm 11ac VHT20_MCS0: -95 dBm 11ac VHT20_MCS8 : -72 dBm 11ac VHT40_MCS0: -92 dBm 11ac VHT40_MCS9: -67 dBm 11ax HE20_MCS0: -95 dBm 11ax HE20_MCS11: -65 dBm 11ax HE40_MCS0: -92 dBm 11ax

Daytech.Az