

PAVA9425E Amplifier

PAVA9425E 4 Zone Expansion Amplifier with Main / Backup Switching

- 4 zones speaker output(could be extended up to 128 zones)
- Built-in 1000W main amplifier and 1000W backup amplifier,with amplifier fault detection
- Support 2 balanced microphone inputs, 4 analog AUX inputs and 1 AUX output
- With master volume control and treble and bass control
- Support paging to specific zone without interrupting background music broadcasting
- With on/off buttons for an independent zone and all zones
- Support expansion amplifier address selection
- Support program source monitoring function
- Support remote computer detection and control
- Support speaker line detection and system detection
- 4 channels dry contact trigger input/output, 4 channels DC24V override output
- Support AC220V and DC24V power supply

Power	1000 W
-------	--------



Ətraflı

Model		PAVA9425E
Rated Output Power		≥1000W (100V)
Input Sensitivity	EMC MIC	—  —

	MIC		5±0.5mV 10kΩ
	LINE		1000±100mV 10kΩ
Harmonic Distortion	EMC MIC		<1% 1kHz
	MIC		1%1khz
	LINE		<1% 1kHz
Frequency Response	EMC MIC		80Hz-15kHz (±3dB)
	MIC		1%1khz
	LINE		50Hz-18kHz (±3dB)
S/N Ratio	EMC MIC		>75dB (A weighted)
	MIC		1%1khz
	LINE		>80dB (A weighted)
EMC LINE AUX OUT	Output Voltage		1000mV
	Frequency Range		80Hz-15kHz±3dB
	Harmonic Distortion		<1% 1kHz
System Connection Control Contact Output/Input	System Fault Relay Output		Short circuit, no voltage
	Emergency Mode Relay Output		Short circuit, no voltage
	Fire Reset Input		Short circuit, t≥0.5S, no voltage
	4-Channel Dry Contact Output		Short circuit, no voltage
	4-Channel Dry Contact Input	Short Circuit Mode	Short circuit input, no voltage
		Level Mode	3.3V~24V

Working Power	AC	AC220V-230V/50-60Hz
	DC	DC 24V/34A
Package Dimensions (L*W*H)		625×635×165mm
Machine Dimensions (L*W*H)		428*430*88mm
Gross Weight		14kg
Net Weight		12.05kg