

Mikrafon PAVA9008

PAVA9008 16 Zones Remote Paging Microphone

- Support 16-zone paging, single- or multi-zone paging, group paging and all-zone paging
- With DIP address settings
- Powered by bus and DC48V
- With 1 AUX IN for paging signal input
- With 2-digit DIP switches for selecting AUX or Local MIC IN
- Support redundant wiring of lines
- The system can support up to 8 devices (remote paging microphones or fireman microphones). With RJ45 ports, these microphones are powered by bus communication port and connected hand in hand
- Support self-defined group functions for buttons
- If the host is connected to a device via a single port, it can support a maximum transmission distance of 600 meters. The host can be cascaded to up to three devices via a single port, with a maximum transmission distance of 300 meters



Ətraflı

Model	PAVA9008
Microphone Input Sensitivity	30mV 600Ω
Line Input Sensitivity	1000mV 10kΩ
Frequency Response	80Hz~15kHz (±3dB)
Distortion	<1%
S/N Ratio	>75dB (A-Weighted)
PoE Power	(48±3)V/0.1A
Phantom Power	-

Expansion Keyboard for Remote Paging Microphone	PAVA9008E
Interface	RJ45
Package Dimensions	415×306×116mm
Machine Dimensions	166×220×54mm
Gross Weight	1.7kg
Net Weight	1.25kg