DAYTECH.AZ

DSP602EN Ceiling Speaker

DSP602EN 6.5 Inch Fireproof Ceiling Speaker

- Adopts the fashionable thin-edge plane big cylinder and the carbon alloy aluminum mesh design
- With the RAL white coating so as to integrate with any indoor place perfectly
- Equipped with a 6.5"unit, full-range designed loudspeaker
- With magnetic circuit encapsulated with special engineering plastic process
- Equipped with fireproof Hood, enhance the protection of electric cable connection terminal



Ətraflı

Model	DSP602EN
Standards	EN44-24: 2008 Loudspeaker for voice alarm
	system for fire detection and fire alarm system
Environmental Class EN54-24	Type A, indoor places
Protection Grade EN60529	IP21C
Ways/Speakers/Type	1 way, double cone full range Ø156mm, 100V system
Transformer	100V,6W-3W-1.5W
In axis frecuency	90-18000Hz
response(±7dB)	
Sensitivity (@1m, 1W)	91 dBSPL(200Hz-10kHz pink noise)
Coverage angle 1kHz(HxV)	180°

$\begin{array}{cccccccccccccccccccccccccccccccccccc$		
$\begin{array}{llllllllllllllllllllllllllllllllllll$	SPL max (@1m, Pmax)	99dB(200Hz-10kHz pink noise)
Dimensions Ø190mm-P=108mm Hole diameter Ø 168-172mm Weight 1.0Kg Material Flame retarding ABS	Nominal power	6W
Hole diameter Ø 168-172mm Weight 1.0Kg Material Flame retarding ABS	Impedance at 1000Hz	180Ω(6W),310Ω(3W),940Ω(1.5W)
Weight 1.0Kg Material Flame retarding ABS	Dimensions	Ø190mm-P=108mm
Material Flame retarding ABS	Hole diameter	Ø 168-172mm
	Weight	1.0Kg
Connections Ceramic connector and thermal fuse	Material	Flame retarding ABS
	Connections	Ceramic connector and thermal fuse

<u>Daytech.Az</u>