

DSP602EN Ceiling Speaker

DSP602EN 6.5 Inch Fireproof Ceiling Speaker

Adopts the fashionable thin-edge plane big cylinder and the carbon alloy aluminum mesh design
With the RAL white coating so as to integrate with any indoor place perfectly

Equipped with a 6.5" unit, full-range designed loudspeaker

With magnetic circuit encapsulated with special engineering plastic process

Equipped with fireproof Hood, enhance the protection of electric cable connection terminal

Power	6W
-------	----



Detailed

Model	DSP602EN
Standards	EN44-24: 2008 Loudspeaker for voice alarm system for fire detection and fire alarm system
Environmental Class EN54-24	Type A, indoor places
Protection Grade EN60529	IP21C
Ways/Speakers/Type	1 way, double cone full range Ø156mm, 100V system
Transformer	100V,6W-3W-1.5W
In axis frequency response(±7dB)	90-18000Hz
Sensitivity (@1m, 1W)	91 dB SPL(200Hz-10kHz pink noise)
Coverage angle 1kHz(HxV)	180°

SPL max (@1m, Pmax)	99dB(200Hz-10kHz pink noise)
Nominal power	6W
Impedance at 1000Hz	180Ω(6W),310Ω(3W),940Ω(1.5W)
Dimensions	Ø190mm-P=108mm
Hole diameter	Ø 168-172mm
Weight	1.0Kg
Material	Flame retarding ABS
Connections	Ceramic connector and thermal fuse

Daytech.Az