

DW2235 Ceiling Speaker

DW2235 6.5 Inch 2x35W 2-Way Stereo WiFi & Bluetooth Ceiling Speaker

- 6.5” Kevlar bass cone driver rubber overhang
- 1” aluminum dome driver EOS waveguide design
- 35W LF @4ohm, 15W HF@8ohm full digital amplifier
- Can hook up a slave speaker to become stereo speakers
- Streaming music via network without distance limitation or Bluetooth 5.0 up to 15 meters
- Spotify connect, Airplay, Qplay, DLNA, UPnP streaming protocols supported
- Support streaming source from online services, smart device, NAS, Bluetooth and Line in
- Multiroom streaming enabled by multiple units connected in same network
- All music sources can be restreamed in sync to other models from us
- Spotify, Deezer, Tidal, Qobuz, Amazon Music, Napster, Pandora, Internet Radio, iHeartRadio, TuneIn, QQMusic, lots of online streaming services integrated to use in the app
- Free iOS and Android app available
- Free global online update for new features
- EQ adjustment via app or remote controller

Power	35W
-------	-----



Ətraflı

Model	DW2235		
Master Speaker (Stereo set / Mono)			
Connections			
Power Supply	24V/4.16A		
Audio Input	AUX (3.5mm)	Max 1V RMS input	
	Buetooth 5.0	AAC FLAC	
Audio Output	Speaker out		
Network	WiFi	2.4G	

		Standard	802.11 b/g/n 1T1R
		Frequency	2.412GHz-2.484GHz
		Transmit	802.11b: +20dBm(Max.)
			802.11g: +18dBm(Max.)
			802.11n: +15dBm(Max.)
		Receive Sensitivity	802.11b: -89dBm
			802.11g: -81dBm
			802.11n: -71dBm
	LAN	RJ45	
Stereo / Mono Switch	Switch Stereo / Mono Output:  Stereo: Master speaker output Right channel, Slave speaker output Left channel  Mono: Left + Right Channel for both speakers		
Mode Button	Change Source Mode: WiFi / BT /AUX in		
Speaker			
Bass	6.5 inch kevlar bass cone driver rubber overhang		
Tweeter	1 inch aluminum dome driver EOS waveguide design		
Sensitivity	Bass: 86±3dB		
	Tweeter: 89±3dB		
Size	23cm×10.5cm (deep)		
Amplifier			
High/Low Frequency	LF 4Ω 35W *2		
	HF 8Ω 15W *2		
Frequency Response	LF: 60Hz-2500Hz HF: 3000Hz-20000Hz		
Signal Noise Ratio	≥85dB		
THD+N	□0.9%		
Crosstalk	□55dB		
Slave Speaker			
Connections			
Audio Input	Speaker out		
Speaker			
Bass	6.5 inch kevlar bass cone driver rubber overhang		
Tweeter	1 inch aluminum dome driver EOS waveguide design		
Sensitivity	Bass: 86±3dB		
	Tweeter: 89±3dB		
Size	23cmx10.5cm (deep)		