

Domofon DS-KV8213-WME1

DS-KV8213-WME1 C İKİ MENZİLLİ İP DOMOFON CAGHIRISH PANELİ HIKVISION

- 2 MP camera with IR supplement
- Two nametag buttons calling design for easier calls
- Built-in card reader module
- Standard PoE power supply
- IK08 & IP65 higher protection level with aluminum alloy material
- Convenient Hik-Connect APP mobile control

Connection type	IP
Device	Call
Memory	Memory
Material	Metal



Detailed

System parameters	
Operation system	Linux
ROM	32 MB
RAM	256 MB
Processor	Embedded highperformance processor
Display parameters	
Screen size	/

Operation method	/
Type	/
Resolution	/
Video parameters	
Lens	1
Resolution	Main stream:1920 × 1080p and 1280 × 720p Sub stream: 640 × 480p
FOV	Horizontal: 124°Vertical: 75°
Wide dynamic range(WDR)	Digital WDR/76.9 dB
Supplement light	IR light, up to 3 m
Video compression standard	H.264
Audio parameters	
Audio input	1 built-in omnidirectional microphone
Audio compression standard	G.711 U, G.711 A
Audio output	1 built-in loudspeaker
Audio compression bitrate	64 Kbps
Audio quality	Noise suppression and echo cancellation
Volume adjustment	Adjustable
Capacity	
User capacity	2000
Card capacity	10000
Linked indoor station capacity	2 (main indoorstation)
Sub door station capacity	16
Network parameters	
Network protocol	TCP/IP, RTSP

Wi-Fi	IEEE802.11b, IEEE802.11g, IEEE802.11n
Bluetooth	/
3G/4G	/
Received frequency	2.4 to 2.4835GHz
Transmitted frequency	2.4 to 2.4835GHz
Bandwidth	20/40 MHz
Frequency power	802.11b:15 dBm+/- 1.5 dBm 802.11g:15 dBm +/- 1.5 dBm 802.11n(ht20):14 dBm +/- 1.5 dBm 802.11n(ht40):12 dBm +/- 1.5 dBm
Authentication	
Card reading frequency	13.56 MHz
Device interfaces	
Alarm input	4
Network interface	1 RJ-45,10/100 Mbps self-adaptive
TAMPER	1
Exit button	2
RS-485	1
USB	/
Wiegand	/
TF card	Reserved
Alarm output	/
Lock control	2 relays, Max. 30 VDC 2 A
Door contact input	2
General	

Button	2 physical buttons
Installation	Surface mounting
Indicator	3
Weight	Net weight:0.370 kg Gross weight: 0.637 kg
Protective level	IP65, IK08
Working temperature	-40 °C to 53 °C(-40 °F to 127.4 °F)
Working humidity	10% to 95% (no-condensing)
Dimension (W × H × D)	174 mm × 91 mm × 29 mm (6.9" × 3.6" × 1.1")
Battery	/
Application environment	Outdoor
Power consumption	□ 10 W
Language	English, French,Portuguese, Portuguese (Brazil), Spanish, Russian, German,Italian, Polish, Arabic, Turkish, Vietnamese, Hungarian, Dutch, Romanian, Czech, Bulgarian, Ukrainian, Croatian, Serbian, Greek, Slovak