

UPS 3KVA UNB1103KS

3KVA/3KW tower type online UPS standard backup

With RS232/USB/EPO/Smart socket

With 6pcs 12V9AH batteries, EU input plug and output socket, 220V/50HZ

Capacity	3KVA
Mode	Online
Form	Tower
Battery	9Ah

**Detailed**

Model	UNB1103KS
Capacity	3kVA/3kW
Input	
Rated Voltage	208/ 220/230/240Vac, L+N+PE
Voltage Range	110~300Vac
Frequency Range	50/60±6Hz
Power Factor	≥0.99
THDi	≤4% (linear load); ≤5% (non-linear load)
Output	
Rated Voltage	208/220/230/240Vac,L+N+PE
VoltagePrecision	±1%
Frequency	50/60Hz ± 0.1%
THDu	≤2% (linear load); ≤5% (non-linear load)
Transfer Time	Zero

Crest Factor	3:1
Overload Capacity (Line Mode)	102%~110% load, 30min;110%~130% load, 10min; 130%~150% load, 30s; >150% load, 200ms
Overload Capacity (Battery Mode)	102%~110% load, 1min;110%~130% load, 10s; 130%~150% load, 3s;>150% load, 200ms
Efficiency	
Line Mode	95.5%
Battery Mode	91.5%
ECO Mode	98%
Battery	
Nominal Voltage	72Vdc
Battery Number	9Ah*6pcs
Charge Current	1A(1-4A)
Communication	
Interface	RS232 / USB/ Snmp Card(optional) /AS400 card(optional)/RS485 card
Environment	
Operation Temperature	0~40°C
Humidity	0~95%(non-condensing)
Noise	≤50dB@1meter away
Altitude	Up to 1000m without derating
Physical	
Dimensions (W*D*H)mm	190*418*322
Weight (kg)	23.5