

DS-PDCO-E-WE Signalizasiya

Signalizasiya DS-PDCO-E-WE Aesthetically appealing design and reliable detection



Ətraflı

Detection Performance	
Detection Method	Carbon Monoxide Sensor
Feature	
Environment Temperature Indicator	Support
Signal Strength Indicator	Support
Self-health Check	Support
Alarm Sound Interlink	Support
Interface	
Power Switch	Power Up Enrolling
LED Indicator	Red (Alarm)
Buzzer	≥ 85dB @ 3 m
Transmission	
Transmission Method	Two-Way RF Wireless
Transmission Frequency	868MHz
Transmission Security	AES-128 Encryption
Transmission Range(Free Space)	1.6Km
Enrolling Method	Power up;Remote ID;QR Code
Electrical Characteristics	
Standard Battery Life	10 years for standalone sensor
	5 years for RF wireless
Power Supply	Battery Powered
Battery Type	Non Replaceable Energizer L91 x 2 for Sensor
	Replaceable CR123A x 1 for RF Wireless

Typical Voltage	3V
General	
Operation Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Operation Humidity	10% to 90%
Dimension(WxHxD)	ø120 × 42mm
Weight	194.5g
Mounting Method	Ceiling
Application Scenario	Indoor