

DS-PDPC12P-EG2-WE Camera

DS-PDPC12P-EG2-WE Wireless PIR-Camera Detector

- Detection range: 12m/85.9°
- Up to 30 kg pet immunity
- SEC (Smart Environmental Control) – Advanced digital signal processing and 3D optics
- Polarizing IR lens design for more uniform night illumination and excellent night shots
- Large integrated memory buffer for image storage
- Fully remote configurable through APP
- Multiple enrollment method and easy installation design
- Easy replaceable battery with PCB protected



Ətraflı

Model	DS-PDPC12P-EG2-WE
Subseries	Motion Detectors
Day/Night Switch	Color/Black & White
Weight	210 g
RF Frequency	868MHz
Application Scenario	Indoor
EN Grade	EN Grade 2
Sensitivity	High;Auto;Pet
Dimension(WxHxD)	72.2 mm × 120.5 mm × 56.7 mm
Detection Method	Passive Infrared;Video Verification
Detection Range	12m

Detection Angle	12m
Detection Zones	52
Detectable Speed	0.3~2m/s
White Light Filter	6500lux
Pet Immunity	30Kg
Digital Temperature Compensation	Support
Digital Processing	Support
Sealed Optics	Support
Tamper Protection	Front;Rear
Environment Temperature Indicator	Support
Signal Strength Indicator	Support
Transmission Technology	CAM-X Wireless
Transmission Method	Two-Way RF Wireless
Transmission Frequency	868MHz
Transmission Security	AES-128 Encryption
Transmission Range(Free Space)	AES-128 Encryption
Enrolling Method	Power up;Remote ID;QR Code
Typical Voltage	3V
Mounting Height	1.8 m to 2.4 m
Mounting Method	Wall
Creep Zone Protection	Support
Bracket	Optional Wall & Ceiling Accessory
Image Type	JPEG
Fill Light	Infrared Light
Fill Range	12m