

DS-PWA96-M-WE Control Panel

DS-PWA96-M-WE AX PRO (868MHz) Simsiz təhlükəsizlik signalızasiya

- TCP/IP, Wi-Fi, and 3/4G network
- New generation wireless protocol: Tri-X/Cam-X
- Long RF transmission distance
- Two-way communication with AES-128 encryption
- Connects up to 96 wireless zones/outputs (including 48 PIRCAMs), 48 wireless keyfobs, 4 repeaters, 6 sounders(3 internal+3 external), 8 tag readers and keypads
- Supports up to 48 network users, including 1 installer, 1 administrator, and 46 normal users
- Voice prompt
- Configuration via Web client, mobile client, and Convergence Cloud
- Hik-Connect and Hik-ProConnect configuration depends on the user access level
- Pushes alarm notification via messages or phone calls
- Views live videos from Hik-Connect
- Alarm video clips via emails and APP
- Supports LED indicator to indicates system status
- 4520 mAh lithium backup battery
- SIA-DC09 protocol, and supports both Contact ID and SIA data format
- Supports Hik-IP Receiver and Hik-IP Receiver Pro for ARC communication



Ətraflı

Software features	
Diagnostics via the APP or Web	Supported
Installer	1
Installer APP for programming	Supported
Onboard video clips	4
Web server for maintenance (offline configuration)	Supported
Wi-Fi standard	Supported
Arm modes	Away/Stay
Firmware upgrade	APP/Web Portal
Admin	1
Wired network	Supported
Programming tools	Hik-Connect/Hik-ProConnect/Web Portal/

	IVMS4200/ Convergence Cloud
Forced arming with open zones	Supported
Memory log stored	5000
User	46
User APP for operating	Supported
Voice prompt	Supported
Area	32
Automatic arm/disarm timers	Supported
<b>Hardware features</b>	
RS232 output	Supported
SIM slot	Dual
3/4G on board	Supported
Tag reader built in	Supported
Loudspeaker built in	Supported
<b>Electrical characteristics</b>	
Battery type	Built in on board Battery Li
Power supply	Built in power supply
Operation temperature	-10 °C to +55 °C (please make sure the adapter is connected)
Battery life span	Up to 12 hours at normal temperature (The battery working time can be significantly reduced at low temperatures)
<b>Wireless transmission</b>	
RF frequency	868 Mhz
RF method	Support
Wireless security	Frequency Hoping 128 AES Encryption
Display	
LEDs status	Arm/Disarm, Alarm, Tamper, Fault, Cloud, Power
<b>General</b>	
Dimension(WxHxD)	170.0 mm (6.7") × 170.0 (6.7") mm × 38.6 mm (1.5")
Shell material	Plastic
Color	White
Weight	557.5 g (19.7 oz)
<b>Device management</b>	
Tag	48
PIR cam	Supported
Zones	96 (up to 48 PIRCAMs)
Keypad	8 (including tag reader)
Wireless sounder	6 (3 internal+3 external)
Wireless repeater	4
Keyfob	48
Multi Transmitter	6
<b>Report method</b>	
ARC protocol	SIA DC09 (SIA level 2, Contact ID), ISUP, ISAPI

	(SDK)  Hik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685)  Supports video verification and remote control	
--	--	--

---