

I-1000-1 Intelligent Adresli Yangın

I-1000-1 Intelligent Addressable Fire Alarm Switch. Intelligent Fire Alarm Panel

- Standard expansion option for 1 circuit and up to 4 circuits
- Advanced Intelligent Communication
- 32 Bit Microprocessor
- Secure and Fast Communication
- Fast Detection and Anti-False Alarm Memory
- Programmable from Panel
- 127 device connections per circuit
- 240x128 Graphic LCD display
- 30 zones and 1 siren line
- Network with all Alfamax Panels
- Ability to store 1500 event records thanks to internal memory
- Programmable with PC software
- Optional panel printer
- Repeater panel input
- Effectiveness Test
- Day and Night Mode



Detailed

Standard	EN54-29
Panel Supply	220 ( +- 10%) VAC 50/60 Hz
Panel Current	0.600A, 2A Sigorta
Operating Temperature	0°C - 40°C (%95 Humidity)
IP Protection	IP30
Application Area	Indoor use

Programming	SenseAction Computer Program
Zone Capacity	up to 30 zones
Loop Information	Single loop, expandable up to 4
Battery	2 pieces 12V 21 Ah dry battery
Repeater Connection	Up to 2000m with 1.5mm 2 cable
Pc connection	with RS232 port
Panel Printer	Optional thermal printer
Dimensions	540x420x175 mm