

## SONORA-4TB Wall Mount Speaker

SONORA-4TB Wall Mount Speaker Weatherproof Loudspeaker

Crisp, distortion-free sound Excellent finish and elegant design

IP-66 protection and salt fog

Quick and easy installation

Power	30W
-------	-----



### Detailed

Type	Low-impedance/broadcast loudspeaker
Power	60 W Max, RMS: 30 W into 8 ohms, 3.75 / 7.5 / 15 / 30 W into 100 V
Speakers	1 x 4" polypropylene woofer 1 x 1" tweeter
Frequency Range	120 - 20,000 Hz
Impedance of Acoustic Low-Impedance Lines	8 Ω
Voltage of acoustic broadcast lines	100 V
Sensitivity	85 dB @ 1 W/1 m
Max. SPL	98 dB @ 1 W/1 m
Opening angles	H/V: 215°/225° @500Hz, 145°/130°@1kHz, 115°/120°@2kHz, 80°/110°@4kHz (-6 dB)

Protection	IP-66 in compliance with EN 60529 IEC 60068-2-11 Environmental Test (Salt mist)
Material	ABS (UV resistance) Aluminium mesh grille, with powder-coated finish Weather-resistant mount Stainless steel screws
Switch	W selector in high Z and low Z
Connectors	Euroblock in and out for cable 0.25 - 2.5 mm <sup>2</sup> cross section
Operating Temperatures	-10°C ~ 60°C
Color	White (RAL 9003)
Dimension	Loudspeaker: 125 x 202 x 125 mm depth Mount wall plate: 68 x 110 mm Loudspeaker with mount: 193 mm depth
Weight	1.5 kg
Montage	Tilt-and-turn bracket, both planes ± 60° Steel cable