

DSP9101 IP Remote Paging Station

DSP9101 IP Remote Paging Station

- 7" TFT true-color LCD + capacitive touch screen supporting five-point touch control.
- Controlling up to 200 partitions with the function of opening all partitions by touching one button.
- The function of partition paging and group partition.
- Displaying the partition and group to be focused on as required.
- Checking the information on status of the partition.
- With the function of multi-section level indication resulting in more intuitive paging sound pressure.
- Broadcasting the songs in the program database of the host to the partitions.
- With the function of keeping every paging record.



Detailed

Model		Parameters
Support Protocol		TCP/IP, ICMP, IGMP (multicast)
AUX IN	Input Impedance	$\geq 10k\Omega$
	Input Sensitivity	-10dB (1V)
	Frequency Response	20Hz-20kHz
AUX OUT	Output Sensitivity	$\geq 100\Omega$
	Output Amplitude	$1.0 \pm 0.1V$
	Frequency Response	20Hz-20kHz
	Distortion	$\leq 0.1\%$
	S/N Ratio	$\geq 81dB$
MIC IN	Input Sensitivity	$40 \pm 10mV$

	Distortion	≤0.5%
	Effective Frequency Range of Gain Limit (±3dB)	80Hz-10kHz
	S/N Ratio (30K low-pass)	≥75dB
Interface	Network Interface	RJ45 (10/100M)
	Audio Unput Interface	3.5mm headphone jack
	Audio Output Interface	3.5mm headphone jack
Others	Input Power	DC12V
	Operating Temperature	-20 - +55°C
	Package Size (H×W×D)	170×290×185mm
	Product Size (H×W×D)	65×240×150mm
	Gross Weight	2.5KG
	Net Weight	1.3KG