

PoE Switch FF-B2421B

FF-2421B PoE Switch 24POE+2FE+1SFP

- 24*10/100mbps POE port, 2*100/1000mbpsUP Link, 1SFP*100/1000mbpsUP Link
- 150m Distance
- Support IEEE802.3AF/AT
- Whole Power:350W(52V 5.76A)
- All port supported by MDI/MDIX auto flip and self negotiation
- Supply 24 10/100Mbps adaptive high speed forwarding data packet non-lost port.
- Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.
- Each port max. power supply reached 30W.

Port Number	24 Port
Port speed	1000mbp/s
PoE	PoE
PoE power	30 W



Detailed

Product	24 Port POE Switch
Model	FF-B2421B
POE Port	1 to 24support IEEE802.3AF/AT Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	Both 1/2+□3/6- and 4/5+7/8-
Whole Power	≤350W (52V 5.76A)
POE Protocol	IEEE 802.3af/IEEE 802.3at
POE Type	End-span
Power Distance	≤150m
Network Standard	IEEE 802.3□ IEEE802.3u□802.3x□802.3af/at
Network Medium	10/100BASE-TX:5 class and above non shielded twisted pair

Data Distance	≤150m
Switch Capability	12.8Gbps
Forwarding Mode	Store and forward
Forwarding Rate	100BASE-tx□14800pps/port
MAC Address	MAC address table 16K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	Each port occupied 1 LINK/ACT.100Mbps, POE Status Indicator, Whole power indicator
Working Environment	Working temperature□-10°-- 55°C
Weight	2.7kg
Size	372×222×45(L*W*H)mm