

PoE Extender FF-DG13G

FF-DG13G 3POE Output+1POE input VLAN POE Extender

- 3*100/1000mbps POE port to output,1*100/1000mbps port to input
- 100m Distance and VLAN,
- Support IEEE802.3AF/AT
- POE In:44V-57V/30W;
- POE Output (1-3) :44-57V /24W
- All port supported by MDI/MDIX auto flip and self negotiation
- Supply 4 100/1000Mbps adaptive high speed forwarding data packet non-lost port.
- Each port average power supply is reached 8W.

Port Number	4 Port
Port speed	1000mbp/s
PoE	PoE
PoE power	30 W



Detailed

Product	100/1000mbps POE Extender
Model	FF-DG13G
POE Port	IEEE802.3AF/AT Standard
Output Power	8W/Per port
Power input Pin	1/2+□3/6- □4/5+□7/8-
Power output pin	1/2+□3/6-
Whole Power	≤30W
POE Protocol	IEEE 802.3af/IEEE 802.3at
Power/Data Distance	≤100m
Network Standard	IEEE 802.3□ IEEE802.3u□802.3x□802.3af/at
Network Medium	10/100BASE-TX:5 class and above non shielded

	twisted pair
Switch Capability	10Gbps
Forwarding Method	100BASE-tx:148800pps/port 1000BASE-tx: 1488000pps/port
Forwarding Rate	7.4Mpps
MAC Address	MAC address table 1K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and back pressure for Half-duplex mode
Working Environment	Working temperature-10°-- 55°C Storage temperature : -40°-- 85°C
Weight	150g±5%
Size	(Length)98mm*(Width)148mm*(High)34mm