

Printer XP-Q838L

XP-Q838L 80mm Thermal Receipt Printer

- Material - ABS
- OEM Availability - Yes
- Certification - CCC, CE, FCC, RoHS, KC, SAA, BIS, BSMI



Detailed

Model	XP-Q838L		
Printing Features			
Printing method	Direct thermal		
Paper width	79.5±0.5mm		
Print width	72mm		
Column capacity	576 dots/line or 512 dots/line		
Printing speed	230 mm/s	260 mm/s	300 mm/s
Interface	USB / Lan / USB+Serial / USB+Lan (Optional:USB+WiFi / USB+Bluetooth)	USB+Serial+Lan (Optional: USB+Serial+Lan+WiFi / USB+Serial+Lan+Bluetooth)	USB+Serial+Lan
Line spacing	3.75mm(Adjustable by commands)		
Column number	80mm paper: Font A - 42 columns or 48 columns / Font B - 56 columns or 64 columns/ Simplified/Traditional Chinese - 21 columns or 24 columns		

Character size	ANK, Font A□1.5×3.0mm(12×24 dots) Font B□1.1×2.1mm(9×17 dots) Simplified / Traditional Chinese:3.0×3.0mm(24×24 dots□		
Barcode Character			
Extension character sheet	PC437(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portugal) / PC863(Canadian) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)		
1D Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128		
2D Barcode	QR CODE / PDF417		
Input buffer	96 Kbytes(USB/Lan/USB+Serial) 128 Kbytes(USB+Lan)	128 Kbytes	4096 Kbytes
NV Flash	256 Kbytes		
Power			
Power adaptor	AC 100~240V, 50□60Hz		
Printer Input	DC 24V/2.5A		
Cash drawer	DC 24V/1A		
Physical characteristics			
Weight	1.0 Kg		
Dimensions	193.76*144.23*133mm(D*W*H)		
Auto cutter	Partial		
Cutter life	1.5 million cuts		
Printer head life	150Km		
Software			
Emulation	ESC/POS		
Driver	Windows/JPOS/Linux/OPOS/Android/Mac		
Utility	Windows & Linux test Utility		
SDK	iOS, Android, Windows		
Environmental Requirements			
Work environment	Temperature (0□45°C) humidity(10□80%)		
Storage environment	Temperature(-10□60°C) humidity(10□90%)		