

Printer XP-Q805K

XP-Q805K 80mm Thermal Receipt Bill Printer

- Interface - USB
- Support both 80mm width paper (300mm/s support)
- Support page mode (300mm/s support)
- Compatible with ESC/POS commands
- Support Windows, Linux, Android, IOS, OPOS and MACOS
- Cutter life 1.5 million cuts
- Auto-cutter
- Wall Mountable
- Printer Headlife - 150KM
- Printing Speed - 230mm/s



Detailed

Model	XP-Q805K
Printing method	Direct thermal
Paper width	79.5±0.5mm
Printing speed	230mm/s
Column capacity	576 dots/line or 512 dots/line
Interface	USB; (Option:USB+Bluetooth / USB+Wi-Fi)
Line spacing	3.75mm(Adjustable by commands)
Character size	ANK, Font A□1.5×3.0mm(12×24 dots) Font B□1.1×2.1mm(9×17 dots)

	Simplified / Traditional Chinese:3.0×3.0mm(24×24 dots)	
Barcode Character		
Extension character sheet	PC437(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portugal) / PC863(Canadian) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)	
1D Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
2D Barcode	QR CODE / PDF417	
Input buffer	96 Kbytes	256 Kbytes
NV Flash	256 Kbytes	
Power		
Power adaptor Input	AC 100~240V, 50/60Hz	
Printer Input	DC 24V/2.5A	
Cash drawer	DC 24V/1A	
Physical characteristics		
Weight	0.85 Kg	
Dimensions	173*127*130mm	
Auto cutter	Partial	
Cutter life	1.5 million cuts	
Printer head life	150Km	
Software		
Emulation	ESC/POS	
Driver	Windows/Linux	
Utility	Windows & Linux test Utility	
SDK	iOS, Android, Windows	
Work environment	Temperature (0~45°C) humidity(10~80%)	
Storage environment	Temperature(-10~60°C) humidity(10~90%)	