

UPS 700VA UNB600

UPS-700VA/360W plastic case,

- Input voltage range: 145-290V,
- Output voltage range: 220v Plus; 10%
- With 12V7AH*1pc
- Output socket*2pcs, EU plug

Capacity	700VA
Mode	Offline
Form	Tower
Battery	7Ah



Detailed

Model	UNB600
Capacity	700VA
Input voltage range	145~290Vac
Output voltage range	220V±10%
Output frequency	47-54Hz(DC Mode)
Wave form	Simulated Sine Wave
Transfer time	Typical 4-6ms, maximum 10ms.
QTY & capacity of battery	1 pc*12V7Ah
Charging period	8 hours recover to 90% capacity
Backup time	10-15 minutes(1PC+19 inch LED Monitor)
USB communication port/RJ11/RJ45	Optional
Automatic charging (offline charging)	Yes
Battery low voltage protection	Yes
Short circuit & Overload protection	Yes

Auto restart while AC is recovering	Yes	
Silence function when the UPS on battery mode	Yes	
Euro output socket	2pcs	
Unit dimension (mm)	320*90*137	
Color box dimension (mm)	370*145*205	
Master box dimension (mm)	390*313*440	
Pcs in one master carton	4	
Gross weight (1pc, kg)	4,5	
Net weight (1pc, kg)	4,1	